

FEATURES

- Finger proof terminals (to VBG4 requirements)
- Flammability rating UL 94-V0
- Cable sizes from 6 to 35mm²
- Mounting method DIN rail (top hat rail)/G-rail
- Grey feed-through terminal block
- Single level
- Screw termination
- Dimensions of 48mm x 8mm

RS PRO, 1 kV Feed Through Terminal Block, Screw Termination

RS Stock No.: 384-6972



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

If you're working with high levels of power, this easy-to-use RS PRO feed through terminal block has an extremely high voltage rating of 1 kV. You can use it to connect wires together quickly, without the need for wiring or soldering.

General Specifications

Colour	Grey
Number of levels	Single
Termination method	Screw Down
Material	Thermoplastic Insulation
Application	Circuit boards and control panels for industrial electronics

Electrical Specifications

Current rating	41A
Voltage rating	1000V
Rated Impulse Voltage	8kV

Mechanical Specifications

Wire size	22AWG to 8AWG
Cable CSA	6mm ²
Dimensions	48mm x 8mm

Approvals

Standard met

UL, CSA, ECLASS 8.1, ETIM 5.0, ETIM 4.0, ETIM 3.0

