# đ

# MANUAL PUMPS



## **Features & Applications**

- Suction type : Manual squeezing type
- Applicable liquids: Kerosene, Diesel, Gasoline, Water(not safe for drinking), Light oils, Chemical insecticides, Soaps, Detergents, Mild acids, Anti-freeze, Liquid waxes
- Non corrosive, Non toxic plastic material construction

# **Specifications**

- Total Length: 530mm(20.9")
- Suction tube Length: 385mm(15.2")
- Suction tube Outer Dia.: 15mm(0.59")
- Discharge Tube Length: 540mm(21.3")
- Discharge Tube Outer Dia.: 12mm(0.47")
- Head Outer Dia. : 51mm(2.01")
- Delivery Volume : About 7LPM(1.9GPM)
- Main Material : P.E
- Net Weight/pc : About 64g(2.3Oz)



## **Features & Applications**

- Suction type: Manual squeezing type
- Convenient one touch stop push button
- Applicable liquids: Kerosene, Diesel, Gasoline, Water(not safe for drinking), Light oils, Chemical insecticides, Soaps, Detergents, Mild acids, Anti-freeze, Liquid waxes
- Non corrosive, Non toxic plastic material construction

## **Specifications**

- Total Length : 610mm(24.0")
- Suction tube Length: 425mm(16.7")
- Suction tube Outer Dia.: 25mm(0.98")
- Discharge Tube Length: 660mm(26.0")
- Discharge Tube Outer Dia.: 19mm(0.75")
- Head Outer Dia.: 60mm(2.36")
- Delivery Volume : About 12LPM(3.2GPM)
- Main Material : P.E
- Net Weight/pc : About 149g(5.3Oz)



# **Features & Applications**

- Suction type : Manual up and down type
- Bung adaptor Inner Dia: 50mm(1.97")
- Applicable supply tank height: 300mm(11.8")~ 390mm(15.4")
- Applicable liquids: Kerosene, Diesel, Gasoline, Water(not safe for drinking), Light oils, Chemical insecticides, Soaps, Detergents, Mild acids, Anti-freeze, Liquid waxes
- Non corrosive, Non toxic plastic material construction

### **Specifications**

- Total Length: 650mm(25.6")
- Suction tube Length: 425mm(16.7")
- Suction tube Outer Dia.: 25mm(0.98")
- Discharge Tube Length: 660mm(26.0")
- Discharge Tube Outer Dia.: 19mm(0.75")
- Head Outer Dia.: 60mm(2.36")
- Delivery Volume : About 12LPM(3.2GPM)
- Main Material : P.E
- Net Weight/pc : About 160g(5.64Oz)



# **Features & Applications**

- Suction type: Manual squeezing type
- Applicable liquids: Kerosene, Diesel, Gasoline, Water(not safe for drinking), Light oils, Chemical insecticides, Soaps, Detergents, Mild acids, Anti-freeze, Liquid waxes
- Non corrosive, Non toxic plastic material construction

# **Specifications**

- Total Length : About 1,823mm(71.8")
- Suction tube Outer Dia.: 12mm(0.47")
- Head Outer Dia. : 46mm(1.8")
- Delivery Volume : About 4LPM(1.1GPM)
- Main Material : P.E.
- Net Weight/pc : About 70g(2.47Oz)



### **Features & Applications**

- Suction type : Manual squeezing type
- Applicable liquids: Kerosene, Diesel, Gasoline, Water(not safe for drinking), Toluene, Thinner, Nitric acid 35%, Hydrochloric acid 35%, Sulfuric acid 35%, Acetic acid 35%
- Non corrosive, Non toxic plastic material constructed

### **Specifications**

- Total Length: 530mm(20.9")
- Suction tube Length: 385mm(15.2")
- Suction tube Outer Dia. : 15mm(0.59")
- Discharge Tube Length: 540mm(21.3")
- Discharge Tube Outer Dia.: 12mm(0.47")
- Head Outer Dia. : 51mm(2.01")
- Delivery Volume : About 7LPM(1.9GPM)
- Main Material : P.E
- Net Weight/pc : About 68g(2.4Oz)