



Datasheet

ENGLISH

Stock No: 137-613

RS Pro White Polyethylene (PE) Rod, 1000mm x 80mm Diameter



Product Details

Polyethylene (PE-UHMW)

Ultra-high molecular weight polyethylene (PE-UHMW)

Good resistance to cold and stress cracking

Shock, abrasion and chemical resistant

Good electrical insulator for components, valves, pumps, fans, chemical tanks

To IEC112/(0303 ti)

White in colour

Max. Service Temp. (Long Term)	100 °C
Elongation	> 350 %
Tensile Strength	40 MPa
Hardness DIN 53 456 (Ball indentation)	62 (Shore D)
Flammability Rating	UL 94 HB
Water Absorption	0.02 % at saturation



ENGLISH

Note

Polyethylene has poor resistance to hot water, and exposure to UV light will result in gradual decomposition

Polyethylene - HDPE & PE-UHMW

Polyethylene is self-lubricating, has good chemical, abrasion and impact resistance and is easy to machine. It is unaffected by most acids, alkalis and chlorinated hydrocarbons.

Specifications:

Colour	White
Length	1000mm
Material	HDPE
Form	Rod
Rod Diameter	80mm
Density	0.95 to 0.96g/cm ³
Tensile Strength	25 MPa
Flammability Rating	UL 94 HB
Maximum Operating Temperature	+90°C
Hardness	50 Ball Indentation
Water Absorption	0.02%
Elongation	350%