

FEATURES

- Insulation Resistance >= 100 MΩ
- Brass nickel plated coupling nut

RS PRO M12 MALE STRAIGHT TO MALE STRAIGHT 5 PIN 5 WIRE 2m 0.25 sq. mm PUR SHIELDED CABLE

RS Stock No.: 2500720



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description ATTRIBUTE 1

M12 Connector Cable Assembly

Brought to you under the trusted RS Brand, this range of M12 connector cable assemblies are commonly used in sensor and automation equipment. Fitted with a secure coupling nut, these RS M12 cable assemblies are an ideal solution for when reliable data transference is needed.

The M12 connector boasts a high degree of environmental protection, and is ideal for industrial use, with applications ranging from process control to commercial electronics.

Features and Benefits:

- Insulation Resistance >= 100 $M\Omega$
- · Brass nickel plated coupling nut

General Specifications

Rated Operational Voltage	60 V
Current Rating	4A
Insulation Resistance	>= 100 MΩ
Temperature Range	-25°C +75°C
Tightening Torque	0.6 Nm
Coding	A-Coded

Material Specifications

Grip Material	PU
Contact	Cu-Zn
Contact Plating	Gold Flash
Contact Carrier	Nylon 66
Grip Color	Black
Coupling Nut	Brass Nickel-Plated

Cable Specifications

Cable Length-L	2 m
Cable Type	5 Core PUR Shielded Multi Strand
Sheath Color	Black
Cross Section of Wire	0.25 sq. mm
Core Dia	1.3 mm


RS PRO M12 MALE TO MALE CONNECTOR



Cable Dia	5.5 ± 0.1 mm		
Shield Details	Braiding (16 x 7 x 0.12mm)		
Protection Category			
Degree of Protection	P67		
Additional Information			
Custom Tariff Number	85369090		
	05505050		

Connection Diagrams / Assembly Diagrams / Illustrations / Accessories

IEC 61076-2-101



All Dimensions are in mm.

Approvals

Standards Met