



### Main

Product line	QO
Product type	Bar

### Complementary

Number of connectors	9
Wire size	AWG 14...AWG 10 copper AWG 12...AWG 10 aluminium AWG 8 aluminium/copper AWG 6...AWG 4 aluminium/copper AWG 14...AWG 12
Provided equipment	2 screw
Bar length	96 mm
Maximum length of segment	80 mm
Device mounting	Direct mounting back of enclosure
Height	11.10 mm
Depth	7.92 mm
Tightening torque	: 20 lb.in, AWG 14...AWG 10, copper : 20 lb.in, AWG 12...AWG 10, aluminium : 35 lb.in, AWG 6...AWG 4

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.762 cm
Package 1 Width	2.159 cm
Package 1 Length	9.652 cm
Package 1 Weight	45.359 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	10.16 cm
Package 2 Width	16.51 cm
Package 2 Length	18.034 cm
Package 2 Weight	548.847 g

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------