

FEATURES

- Hook up wire is frequently used in control panels, automotive, meters, ovens, internal wiring of computers, electronic equipment, business machines and appliances.
- MPPE insulation
- Easy to handle, strip and terminate
- UL Style 11028
- Flammability Test: VW-1
- Rated Voltage: 600V
- Rated Temperature: 105°C
- Size(AWG):12

RS PRO UL11028 Red, 3.3 mm² Hook Up Wire, 30.5m

RS Stock No.: 208-1060





RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Hook up wire is frequently used in control panels, automotive, meters, ovens, internal wiring of computers, electronic equipment, business machines and appliances.

General Specifications

Type	Equipment Wire/ hook-up wire
Cores Number	1C
Conductor Material	Tinned Copper
Cross Sectional Area	3.3mm ²
Conductor Size of Strands	0.25±0.008mm
Conductor Number of Strands	65
Conductor Strand diameter (mm)	2.36mm
American Wire Gauge	12
Insulation Material	MPPE
Insulation Colour	Red
Insulation Wall Thickness	0.30mm
Insulation Min Thickness	0.22mm
Insulation Diameter	2.97±0.15mm
Wire Style	UL11028
Fire Behaviour	Flammability Test: VW-1
Cable Marking	E254881  AWM STYLE 11028 12AWG 105°C 600V VW-1 c  AWM I A 105°C 600V FT1 -LF- - HF- ELETECK

Electrical Specifications

<i>Voltage Rating</i>	600V
<i>Conductor Resistance</i>	5.74Max Ohms/1000m @ 20degC
<i>Spark Test</i>	1500 VAC RMS
<i>Minimum Bend Radius</i>	15 x overall diameter

Operation Environment Specifications

<i>Minimum Operating Temperature</i>	-40°C
<i>Maximum Operating Temperature</i>	105°C
<i>Operating Temperature Range</i>	-40°C to 105°C

Approvals

<i>Compliance/Certifications</i>	UL 11028
<i>Standards Met</i>	RoHS Compliant
<i>Declarations</i>	REACH