



ENGLISH

Datasheet

RS Pro Yellow Water Hose





Datasheet

RS Pro yellow water hose is the ideal choice for heavy-duty watering and irrigation applications. Resistant to kinking, bending and pulling its multi-layered construction gives it excellent flexibility, wear and weather resistance. The inner core has been designed to optimise water flow while the outer shell is abrasion, UV and crush resistant making it ideal choice for harsh environments.

Key Features:

- Made in the UK
- UV resistant
- DEHP and Phthalate Free
- Highly flexible – ease of handling
- Abrasion and kink resistance
- Ultra smooth liner ensuring water flow performance
- Resistant to repeated pulling, bending, crushing
- Working Temperature range -15°C to +65°C
- 3:1 Safety Factor

Application Examples:

- Farms
- Agriculture
- Horticulture
- Fruit growers
- Vegetable growers
- Garden Centres and Nurseries
- Golf clubs
- Sports clubs
- Landscapers
- Water delivery for Industry, Construction, Local Authorities
- Gardening

Specification:

| RS Stock Number | Internal Diameter | External Diameter | Length | Wall Thickness | Max Working Pressure | Burst Pressure | Bend Radius |
|-----------------|-------------------|-------------------|--------|----------------|----------------------|----------------|-------------|
| 9175119 | 12.5 mm | 17.5 mm | 25 m | 2.5 mm | 16 bar | 48 bar | 100 mm |
| 9175112 | 19 mm | 25.5 mm | 25 m | 3.25 mm | 39 bar | 39 bar | 160 mm |
| 9175116 | 25 mm | 32.5 mm | 25 m | 3.75 mm | 24 bar | 24 bar | 200 mm |
| 9175125 | 12.5 mm | 17.5 mm | 50 m | 2.5 mm | 16 bar | 48 bar | 100 mm |
| 9175128 | 19 mm | 19 mm | 50 m | 3.25 mm | 39 bar | 39 bar | 160 mm |
| 9175122 | 25 mm | 32.5 mm | 50 m | 3.75 mm | 24 bar | 24 bar | 200 mm |