# Eaton SC-35

# Catalog Number: SC-35

Eaton Bussmann series SC fuse, Current-limiting time-delay fuse, Rejection style, 35 A, Class G, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 10 kAIC at 300 Vdc|100 kAIC at 480 Vac, Standard, 480 V, 300 Vdc

#### General specifications

Product Name

Catalog Number

Eaton Bussmann series SC fuse

SC-35

UPC

EAN

051712250351

5027590408424

Product Length/Depth

Product Height 2.25 in

0.41 in

Product Weight

Product Width 0.41 in

0.35 lb

Warranty

Compliances

Not Applicable

CE Marked

RoHS Compliant





# Electrical rating

Amperage Rating

35 A

Interrupt rating

100 kAIC at 480 Vac 10 kAIC at 300 Vdc

Response time

12 sec at 200%

Voltage rating

480 Vac, 300 Vdc

## Physical details

Packaging type

Standard

## General information

Class

Class G

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Special features

Ferrule design, Type P

#### Resources

#### Catalogs

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - SC-35

Technical data sheets

Bussmann series SC Class G Fuse Data Sheet No. 1024

SC-35~BUSS SC FUSE CLASS G CLASS G

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia