


05S 80-350



PU

Standard	Result
T/ZSJL 001-2019	✓
T/ZSJL 002-2019	✓
T/ZSJL 003-2019	✓

* Remark: Please refer to the standard of Zhongshan caster industry association.

Wheel: Thermoplastic polyurethane (PU).
Wheel surface hardness: 98-100° Shore A.
Wheel core structure: polypropylene (PP).
Bearing: SUPO customization ball bearing with dust cover.
 For more information please refer to page299.

Thread Stem	Wheel Material	NO. Model	Wheel Dia (mm)	Tread Width (mm)	Load Capacity (kg)	Load Height (mm)	Swivel Radius (mm)	Brake Swivel Radius (mm)	Bearing	Thread Size (mm)
	(PU)	C05S-02-75-202	75(3")	38	133	112	75	108		M16x35
		C05S-02D-75-202								
		C05S-02-100-202	100(4")		170	137	88	114		
		C05S-02D-100-202								
		C05S-02-125-202	125(5")		205	164	106	127		
		C05S-02D-125-202								
C05S-02-150-202	150(6")	235	191	118	130					
C05S-02D-150-202										

Others (MOQ)

Side lock brake(metal)	Swivel(Hollow Rivet)	Swivel(Hollow Rivet) with Total lock brake(Plastic)	Swivel(Hollow Rivet) with side lock brake(Metal)
C05S-02C-75-202	C05S-03-75-202	C05S-03D-75-202	C05S-03C-75-202
C05S-02C-100-202	C05S-03-100-202	C05S-03D-100-202	C05S-03C-100-202
C05S-02C-125-202	C05S-03-125-202	C05S-03D-125-202	C05S-03C-125-202
C05S-02C-150-202	C05S-03-150-202	C05S-03D-150-202	C05S-03C-150-202

- Customization
- 01 series
- 03S series
- 05S series**
- 07S series
- 08 series
- 09C series
- 10 series
- 11 series
- 12 series
- 13 series
- 17 series
- 20 series
- 21 series
- 23 series
- 24 series
- 27series
- 28 series
- 30 series
- 35 series
- 43 series
- F02 series
- L01 series