

Datasheet

RS Pro M32 Grey EPDM Cable Gland, 15 to 20mm Cable Dia Range, IP67

RS Stock No: **279-7065**



Product Details

RS Pro cable gland in grey colour, has a thread size of M32. This cable gland has a diameter ranging from 15 to 20 mm. The cable features halogen free rubber (EPDM) membrane cable grommet providing protection up to IP67.

Features and Benefits

- Halogen free rubber (EPDM) membrane cable grommet providing protection up to IP67
- Quick and low-cost method of feeding cables through panels
- Ideal for applications where space is restricted
- Tapered top provides a degree of retention and sealing

Specifications:

Cable Diameter Range	15 to 20 mm
Colour	Grey
IP Rating	IP67
Material	EPDM
Maximum Cable Diameter	20 mm
Maximum Operating Temperature	+70°C
Minimum Cable Diameter	15 mm
Minimum Operating Temperature	-50°C
Operating Temperature Range	-50 to +70°C
Thread Size	M32

EPDM Rubber, RAL 7035 Grey, IP 67 (EN 60529), Wall thickness 0,5 - 5 mm, Temperature range -40°...+110°C										
Code	Order symbol	EAN	Size	Cable diameter	A mm	B mm	Da mm	H mm	H1 mm	Pcs/pack
3545078	FEM 4-7	6418074035417	M12	4-7	12,5	0,5-2	20	12,7	5,4	50
3545079	FEM 5-9	6418074035424	M16	5-9	16,5	1-4	21	18	10,5	50
3545278	FEM 4-7 L	6418074070449	M12	4-7	12,5	2-5	20	12,7	5,4	50
3545279	FEM 5-9 L	6418074070456	M16	5-9	16,5	2-5	21	18	10,5	50
3545080	FEM 8-13	6418074035448	M20	8-13	20,5	1-4	25,5	20	12,7	50
3545081	FEM 10-14/PG 16	6418074035455	M23/PG16	10-14	23	1-4	28	21,6	14,7	50
3545082	FEM 11-17	6418074035462	M25	11-17	25,5	1-4	30,5	21,6	14,5	50
3545083	FEM 15-20	6418074035479	M32	15-20	32,5	1-4	38,5	24,8	17,5	25
3545084	FEM 19-28	6418074035486	M40	19-28	40,5	1-4	48,5	30	20,4	25
3545085	FEM 27-35	6418074035530	M50	27-35	50,5	1-4	60,5	35	23,9	10
3545103	FEM 34-45	6418074070852	M63	34-45	63,5	1-4	73,5	40	28,9	5
3546151	MFM 8-12	6418074036803	M50	3x 6-10, 3x 10-14	50,5	2-6	58	20	9	1

