



### Main

|                           |   |
|---------------------------|---|
| Range                     | ZENcelo   |
| Product or component type | Shaver socket   |
| Installation direction    | Vertical  |
| Input voltage             | 240 V AC 50 Hz  |
| Output voltage            | 115 V AC 50 Hz<br>240 V AC 50 Hz  |
| Material                  | Polycarbonate: base<br>Polycarbonate: grid plate<br>Polycarbonate: surround |
| Colour tint               | Silver bronze   |

### Complementary

|                               |  |
|-------------------------------|--|
| Device mounting               | Surface<br>Flush                       |
| Cable cross section           | 1...2.5 mm <sup>2</sup>                |
| Rated operational power in VA | 20 VA                                  |
| Connections - terminals       | Pillar terminal without pressure plate |
| Electrical insulation class   | Class B                                |
| Width                         | 147 mm                                 |
| Height                        | 87 mm                                  |
| Depth                         | 49.3 mm                                |

### Environment

|                                       |                 |
|---------------------------------------|-----------------|
| Ambient air temperature for operation | -5...40 °C      |
| Relative humidity                     | 0...95 %        |
| Environmental characteristic          | No UV resistant |
| Operating altitude                    | <= 2000 m       |
| IP degree of protection               | IP21            |
| Standards                             | IEC 61558-1     |

### Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 0.8 cm    |
| Package 1 Width              | 8.7 cm    |
| Package 1 Length             | 14.7 cm   |
| Package 1 Weight             | 605.66 g  |
| Unit Type of Package 2       | CAR       |
| Number of Units in Package 2 | 20        |
| Package 2 Height             | 16.3 cm   |
| Package 2 Width              | 33 cm     |
| Package 2 Length             | 50.4 cm   |
| Package 2 Weight             | 12113.2 g |
| Unit Type of Package 3       | PAL       |
| Number of Units in Package 3 | 400       |
| Package 3 Height             | 86 cm     |

|                  |          |
|------------------|----------|
| Package 3 Width  | 80 cm    |
| Package 3 Length | 120 cm   |
| Package 3 Weight | 242264 g |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|