SA 5000i cc/cv

MULTI-PROCESS WELDERS

Ouick Specs

Heavy Industrial Applications Fabrication and Construction Heavy Manufacturing Maintenance/Repair Shipbuilding **Refineries and Foundries** Pressure Tank/Vessel Fabrication

Power Voltage 3 Phase AC415V ±15% 50/60Hz **Input Current** 33.9A/24.4kVA

Output Current MIG: 60-500A MMA: 60-400A **Output Voltage** 15-40V OCV: 65VDC

Duty Cycle 60% Weight 41KG

Dimensions D660×H685×W345MM

Wire Feed Speed F-55 3.0-24m/min

FEATURES

- Flexible Multi-Process Capability Including stick, DC TIG, MIG, and flux-cored welding.
- Voltage control gives you the flexibility to manually set the machine when welding aluminum, stainless steel, or anytime you want to set your own parameters on mild steel.
- Thermal overload protection with indicator light helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.
- Inverter-based, DC power source has a simple-to-use operator interface providing only the necessary controls in a compact machine.
- Digital voltmeter and ammeter are easy to
- High efficiency (85%) and high power factor (0.93)

PROCESSES

MIG Flux-Cored Stick DC TIG



INCLUDED

SA 5000i Machine Only Includes:

- SA 5000i with 5M wire feeder
- 3M P-350 MIG TORCH.
- 2.5M work cable and
- 36V CO₂ regulator.











*Please note that the specification may vary within each country. Specifications are subjected to change without notice.

AUSTCORP MANUFACTURING SDN. BHD.

NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3 TAMAN BATU GAJAH PERDANA 31550 PUSING PERAK MALAYSIA TEL: (605)3632 115 FAX: (605)3632 111

E-mail: austcorp@welding.com.my WEB: www.welding.com.my

