

RS PRO Inductive Sensor

RS Stock No.: 2522030

FEATURES

- Non contact detection, safe and reliable;
- ASIC design;
- Perfect choice for metallic target detection.



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Specifications

Mounting	Flush
Rated distance Sn	0.8mm
Assured distance Sa	0...0.64mm
Shape size	M4*30mm
Output	PNP NO
Supply voltage	10...30 VDC
Standard target	Fe 5*5*1t
Switch point offset[%/Sr]	≤ ±10%
Hysteresis range [%/Sr]:	1...20%
Repeat accuracy	≤3%
Load current	≤100mA
Residual voltage	≤2.5V
Current consumption	≤10mA
Protection circuit:	Reverse polarity protection
Output indicator:	Red LED
Ambient temperature	-25°C...70°C
Ambient humidity	35-95%RH
Switch frequency	2000Hz
Voltage withstand	...
Insulation resistance	≥50MΩ (500VDC)
Vibration resistance	10...50Hz(1.5mm)
Housing material	Stainless steel
Connection	2m PUR cable

Protection Category

IP Rating IP67

Additional Information

Custom Tariff Number/HS code 903180

Approvals

Compliance/Certifications CE

Dimension and Wiring