## LV432570

# interphase barriers - 0<630A - set of 6



#### Main

Product or component type	Interphase barrier
Range compatibility	ComPacT new generation ComPacT NSX400 new generation
	ComPacT new generation ComPacT NSX630 new generation
	ComPacT new generation ComPacT NSX DC new generation NSX400 DC
	ComPacT new generation ComPacT NSX DC new generation NSX630 DC
	ComPact ComPact NSX400
	ComPact ComPact NSX630
	ComPact Compact NSX400 DC
	ComPact Compact NSX630 DC
	EasyPact EasyPact CVS400
	EasyPact EasyPact CVS630
	PowerPact PowerPact L
	ComPact Compact INV
	ComPact ComPacT INS
Accessory / separate part type	Insulation accessories
Quantity per set	Set of 6

#### Complementary

Product compatibility	Circuit-breaker
	Plug-in base

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.0 cm	
Package 1 Width	13.2 cm	
Package 1 Length	13.5 cm	
Package 1 Weight	165.0 g	
Unit Type of Package 2	S03	
Number of Units in Package 2	45	
Package 2 Height	30.0 cm	
Package 2 Width	30.0 cm	
Package 2 Length	40.0 cm	
Package 2 Weight	7.9 kg	

### Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
PVC free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Warranty 18 months