



Main

| | |
|----------------------------|------------------------|
| Range | S-Classic |
| Product or component type | Switched socket |
| Device application | Power supply |
| Outlet poles configuration | 2P + E |
| Rated current | 15 A at 230 V AC 50 Hz |
| Quantity per set | Set of 1 |

Complementary

| | |
|---------------------|---|
| Device presentation | Complete product |
| Number of gangs | 1 gang |
| Device mounting | Surface Flush |
| Material | Plate: PC (polycarbonate), white Dolly: PC (polycarbonate), white Base: PP (polypropylene), black |
| Embedding depth | 21.3 mm |
| Height | 87 mm |
| Width | 87 mm |
| Depth | 37.6 mm |



Environment

| | |
|---------------------------------------|-----------------------------|
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Standards | SS 472 MS 1577 BS 546 |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.7 cm |
| Package 1 Width | 8.6 cm |
| Package 1 Length | 8.6 cm |
| Package 1 Weight | 71.0 g |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |

| | |
|----------------------------|---|
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
