



**ENGLISH** 

### **Datasheet**

# RS PRO 2 WAY, 2 ROW, STRAIGHT, SPRING LOADED MALE, .100" [2.54mm] PITCH, PCB

Stock No: 2272143, 2272144



#### **Product Details:**

RS PRO Pogo Pins and Connectors (spring loaded terminals) consist of a pin, barrel, and steel spring with or without an insulator carrier. They are used in many industries across a wide range of applications to make a secure, high reliability connection. This series is highly customizable to meet specific stroke lengths, heights, and electrical capabilities. High-temp plastics are used for our insulators and unlimited molding designs allow for many different shapes and styles to be created for specific applications.

#### **Features & Benefits:**

- High reliability, corrects connection between uneven surfaces and satisfies high vibration connection requirements.
- Increased durability for heavy duty applications Highly Customizable-
- Size, stroke, shape, pin count, etc.
- Low Cost and Easily Integrated

Material:

Insulator: PA46, rated UL 94V-0, Color: Black

Contacts: Copper Alloy Spring: Stainless Steel

Plating:

Gold flash over Nickel underplate overall

**Electrical:** 

Voltage rating: 12 Volts

Current rating: 1A max (3.30mm), 3A max (4.30&5.30mm)

Contact resistance @ working stroke: 20 mohms max. before test

60 mohms max. after test

Insulation resistance: 100 Mohms min

Dielectric withstanding voltage: 100 VRMS @ 60HZ

Mechanical:

Spring force: 90±20gf @ 1.0mm working stroke (3.30mm)

70±20gf @ 1.0mm working stroke (4.30 & 5.30mm)

Full stroke: 1.40mm

Life test: 10,000 Cycles Min


**Temperature Rating:** 


Operating temperature: -30°C to +85°C


**Environmental:** 


Lead free, RoHS compliant.


## **Dimensional line drawings**











3.30mm Length

Example: PH2-3B-08-MVP-3345 = 2X4 PIN

| BOTOTOM CONT. OF BOTOTO BOTOTOM BONDS TO SERVED |                   |  |
|-------------------------------------------------|-------------------|--|
| ADAM P/N                                        | Initial<br>Height |  |
| PH2-3B-XX-MVP-3345                              | 4.5mm             |  |
| PH2-3B-XX-MVP-3350                              | 5.0mm             |  |
|                                                 |                   |  |

4.30mm Length Example: PH2-3B-08-MVP-4355 = 2X4 PIN

| ADAM P/N           | Initial<br>Height |
|--------------------|-------------------|
| PH2-3B-XX-MVP-4355 | 5.5mm             |
| PH2-3B-XX-MVP-4360 | 6.0mm             |

5.30mm Length

| ADAM P/N           | Initial<br>Height |
|--------------------|-------------------|
| PH2-3B-XX-MVP-5365 | 6.5mm             |
| PH2-3B-XX-MVP-5370 | 7.0mm             |
| PH2-3B-XX-MVP-5375 | 7.5mm             |
| PH2-3B-XX-MVP-5380 | 8.0mm             |





