

Datasheet

RS PRO DIN JACK SCREW LOCK

Stock No: 210-0194



Technical Specifications:

To include attributes e.g. height, width, depth, color etc.

Connector type:	Jack
Mounting type:	Cable
Female	IP40
Contact Gender:	Female
Number of Contact:	3~8

Dimensional line drawings

See examples on Brandzone

SECTION A-A

No.	Description	Material	Treat	Qty
1	Housing Holder cap	Zn Alloy	Nickel Plt	1
2	Housing Holder W	Zn Alloy	Nickel Plt	1
3	Screw Cap	Brass	Nickel Plt	1
4	Spring holder	TPS		1
5	Spring	PA6		1
6	Cable Holder	Steel	Nickel Plt	1
7	Spring	Steel	Nickel Plt	1
8	Housing	PA6		1
9	Terminal	Brass	Ag / Sn	4x10000

Specifications
 rating : 250V AC 5A MAX
 contact resistance : 10mΩ MAX shell-50mΩ MAX
 insulation resistance : 1000MΩ MAX @200V DC
 Protection Degree : IP43
 Cable Outlet : 3-6mm

DP563JA	DP564JA	DP565JA	DP566JA	DP567JA	DP568JA

REV	ITEM	REV	DATE	BY	CHK	DATE	BY	CHK
001	001	001	001	001	001	001	001	001

AS "TABLE A"