

#### **FEATURES**

- IP54 performance
- Highly Flexible
- High mechanical strength
- -15°C to +70°C
- Manufactured to BS EN 61386

# RS PRO PVC Coated Galvanised Steel Flexible Conduit 25mm – 10 metres

**RS Stock No.:** 2149582



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

**Product Description** 

. \_\_\_\_ .

## Flexible Conduit



## **General Specifications**

Material	Galvanised Steel with PVC cover			
Colour	Black			
Conduit Type	Flexible			
IP Rating	IP54			
Length	10 m			
Maximum Operating Temperature	+70°C			
Minimum Operating Temperature	-15°C			
Nominal Diameter	25mm			
Internal Diameter (ID)	20.9mm			
Outside Diameter (OD)	25.7mm			

### **Compatible Glands**

Stock No.	Brand	Product Name	Attribute 1	Attribute 2	Attribute 3
2149561	RS PRO	NPB Fixed Gland	2 part gland	High mechanical strength	-100°C to +300°C
2149562	RS PRO	NPB Swivel Gland	2 part gland	High mechanical strength	-100°C to +300°C