

FEATURES

- Dual action lid
- Edge to Edge PCB
- Fast assembly
- No internal corner pillars
- Multiple PCB mounts

RS PRO General Purpose Enclosures

2213552



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

This UK manufactured universal enclosure has been designed to provide flexibility and increased functionality. A unique, dual action lid and clip-in-points for your PCB, reduces assembly time whilst providing the end user with a premium quality, modern product. Moulded from ABS UL94-V0 material, in a variety of sizes and colours, with optional DIN Rail / wall mount brackets available. If you need an enclosure that can handle your electronic applications whilst looking good, then look no further!

General Specifications

| Model Number (p) | | | | | |
|-----------------------------------|--|--|--|--|--|
| Range | Easy Assembly Electronics Enclosure | | | | |
| Use | IIoT/Sensor/Universal/general purpose | | | | |
| Body Material | Flame Resistant ABS | | | | |
| Colour | White | | | | |
| Lid Colour | White | | | | |
| Handheld | No | | | | |
| Flanged | No | | | | |
| Shielded | No | | | | |
| Number of Knockouts | 0 | | | | |
| Transparent Door | No | | | | |
| Explosion Proof | No | | | | |
| RAL Code | RAL 9003 | | | | |
| Design | | | | | |
| Features | Dual action lid, edge to edge PCB, No internal pillars, Fast assembly, Pi compatible | | | | |
| Cover Screws Material | Stainless Steel | | | | |
| Temperature Range (Continuous) | -10°C to 80°C | | | | |
| Temperature Range (Short Term) | | | | | |

Electrical Specifications

Electrical Insulation

Mechanical Specifications Gasket Material N/A External Height 40mm

General Purpose Enclosures



| External Length | 90mm |
|--------------------|--------------------|
| External Width | 60mm |
| External Dimension | 90mm x 60mm x 40mm |
| Weight | 61g |
| Area | |
| Thickness | |

| Protection Category | |
|---------------------|------|
| IP Rating | IP40 |
| IK Rating | IK06 |

| Additional Information | |
|------------------------|------------|
| EAN | |
| Custom Tariff Number | 3926909790 |

Classification

| eCl@ss (Version) | |
|------------------|--|
| UNSPSC (Version) | |

Approvals

| Declarations | |
|------------------------------|--|
| Hazardous Area Certification | |
| Standard Met | |
| European Safety Standard | |

Products

| Stock No. | Brand | Product Name | Body Material | Colour | Shielded |
|-----------|--------|---------------------------------|---------------|--------|----------|
| 2213552 | RS PRO | General Purpose Enclosure | ABS | White | No |
| | | | | | |



Including: Enclosure with singular screw