

| Model No. (Quick disconnected tab) | Rated Frequency ±500(Hz) | Tone | Minimum Sound Pressure L level at 30 cm | | Operating Voltage Range *AC/DC Non-polar All others DC only | | Current Consumption (mA) | | Case Style | | Packing Quantity (Pcs/Box) |
|---------------------------------------|-----------------------------|-------------------------|---|----------|---|-------|--------------------------|----------|------------|-------------|----------------------------|
| | | | At Min V | At Max V | Min V | Max V | At Min V | At Max V | Side View | Bottom View | |
| KPEG650 | 2800 | Continuous | 84 | 97 | 4 | 28 | 2 | 22 | D | 3 | 40 |
| KPEG651 | 2900 | Fast Pulse | 70 | 82 | 6 | 28 | 2 | 11 | D | 4 | 40 |
| KPEG653 | 2900 | Slow Pulse | 71 | 82 | 6 | 28 | 2 | 11 | D | 4 | 40 |
| KPEG655 | 2800 | Continuous + Fast Pulse | 76/74 | 88/86 | 6 | 28 | 4/2 | 16/16 | D | 5 | 40 |
| KPEG657 | 2800 | Continuous + Slow Pulse | 78/71 | 92/87 | 6 | 28 | 3/2 | 18/11 | D | 5 | 40 |
| KPEG650A | 2800 | Continuous | 88 | 98 | 6 | 28 | 5 | 22 | D | 3 | 40 |
| KPEG651A | 2800 | Fast Pulse | 80 | 97 | 6 | 28 | 2 | 12 | D | 4 | 40 |
| KPEG653A | 2800 | Slow Pulse | 80 | 92 | 6 | 28 | 4 | 32 | D | 4 | 40 |
| KPEG655A | 2800 | Continuous + Fast Pulse | 82/76 | 92/86 | 6 | 28 | 3/2 | 29/26 | D | 5 | 40 |
| KPEG657A | 2800 | Continuous + Slow Pulse | 84/77 | 97/92 | 6 | 28 | 5/3 | 17/18 | D | 5 | 40 |
| KPEG650AN | 2800 | Continuous | 70/70 | 87/87 | *4 | 28 | 2/1 | 18/12 | D | 3 | 40 |
| KPEG651AN | 2800 | Fast Pulse | 70/67 | 85/83 | *6 | 28 | 5/4 | 23/18 | D | 4 | 40 |
| KPEG653AN | 2800 | Slow Pulse | 70/67 | 85/83 | *6 | 28 | 5/4 | 23/18 | D | 4 | 40 |
| KPEG610AN | 2800 | Continuous | 79/78 | 90/89 | *30 | 120 | 4/3 | 15/14 | D | 3 | 40 |
| KPEG611AN | 2800 | Fast Pulse | 70/68 | 86/84 | *30 | 120 | 5/5 | 20/17 | D | 4 | 40 |
| KPEG613AN | 2800 | Slow Pulse | 70/68 | 86/84 | *30 | 120 | 5/5 | 20/17 | D | 4 | 40 |
| KPEG648 | 2800 | Continuous | 66 | 86 | 10 | 48 | 3 | 16 | D | 3 | 40 |
| KPEG620AN | 2800 | Continuous | 76/75 | 87/86 | *60 | 250 | 1/1 | 18/7 | E | 3 | 40 |
| KPEG621AN | 2800 | Fast Pulse | 68/68 | 77/77 | *60 | 250 | 4/4 | 5/5 | E | 4 | 40 |
| KPEG623AN | 2800 | Slow Pulse | 71/72 | 85/86 | *60 | 250 | 3/4 | 14/15 | E | 4 | 40 |
| KPEG660 | 1500 ~ 4000 | Siren | 92 | 99 | 6 | 15 | 60 | 160 | E | 3 | 40 |
| KPEG680 | 2000 / 2800 | Hi-Low | 74 | 99 | 6 | 15 | 10 | 90 | E | 3 | 40 |


KPEG650 series fit 1.125 inch (28.57 mm) diameter opening in panels to 0.125 inch (3.17 mm) thick.
Pulse Rate at 12 VDC: 3.0 ± 20% Hz (Fast pulse) 1.2 ± 20% Hz (Slow pulse)

Shape




KPEG650/650A KF
KPEG650AN/610AN KF
KPEG648 KF

Dimension



Bottom View 3



Top View