NSYPLM64G

Wall mounted polyester enclosure, Thalassa PLM, plain door, 647x436x250mm, IP66, IK10, RAL 7035





Main

Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	647 mm
Nominal width	436 mm
Nominal depth	250 mm
Enclosure mounting	Wall mounted
Device composition	1 body
•	1 door
	2 lock
Door type	Plain
Lock type	3 mm double-bar lock

Complementary

Number of locks	2	
Mounting plate description	Without mounting plate	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Polyester reinforced with fibreglass	
Colour	Grey (RAL 7035)	
Standards	NEMA classification 13 NEMA classification 4X IEC 62208	
Product certifications	UL	
Electrical insulation class	Class II	

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for operation	-4080 °C

Packing Units

PCE
1
27.5 cm
46.0 cm
71.0 cm
12.341 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile