

FEATURES

- Momentary foot switch controller
- Rated at 250V ac/30V dc 3A
- Incorporates a non-slip base pad and footpad
- Ideal for machine control applications
- Sealed to IP40
- Operating Temperature: -5°C to 40°C
- Grey cover with a black base

RS PRO General Purpose Momentary Foot Switch - Mild Steel Case Material, Single Pole Single Throw (SPST), 3 A Contact

RS Stock No.:665-922



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description ATTRIBUTE 1

RS PRO treadle foot switch is an extended foot switch which has been designed to incorporate two non-latching foot switches (see stock no. [316-901](#)) connected in parallel. These switches have been constructed from steel and are extremely reliable. This light duty foot switch has SPST N/O contacts and is black and grey in colour.

General Specifications

Contact Configuration	Single Pole Single Throw (SPST)
Switch Operation	Momentary
Case Material	Mild Steel
Switch Environment	General Purpose
Contact Material	Silver
Colour	Black, Grey
Applications	Foot switches are commonly used in applications where hands-free control is more practical or safer. They can be found on: Industrial machinery and smaller power tools, Hospital beds, Dentist Chairs, Lamps
Cable Connection	2metres of 3-core cable

Electrical Specifications

Contact Voltage Rating (AC)	250V
Contact Voltage Rating (DC)	30V
Contact Current Rating	3A

Mechanical Specifications

Length	760mm
Height	28mm
Dimensions	760mm x 95mm x 28mm
Width	95mm

Operation Environment Specifications

Operating Temperature	-5°C to 40°C
------------------------------	--------------

Protection Category

IP Rating	IPX2
------------------	------

Approvals

Standards Met	2014/35/EU, EN 60950
Compliance/Certifications	EN 61058-2-1; EN 61058; EN 60601-1; EN 60950, RoHS



