



ENGLISH

Datasheet

**RS Pro Aluminium Enclosure, IP66, 98 x 64 x 34**

RS Stock No: **760-8976**



## Product Details

RS Pro enclosure measuring 98 x 64 x 34 mm, is IP66 rated and specifically designed for harsh and demanding applications. This watertight series of enclosure is made from die cast aluminium (ALSi12) and it comes with a powder coated grey finish. The enclosure includes a lid and base, captive stainless steel lid screws, a neoprene O-Ring continuous gasket and 4 copper plated earthing screws for grounding. The enclosure meets DIN1725, IEC 60529, NEMA 4X and 6P, UL 508A, UL 50, UL 50E, CE, MIL-STD-810G (Mechanical Vibration and Shock Test), ASTM B117, IEC 62262 and IK 60068-2-75 standards.

## Features and Benefits

- Cover seal temperature stability -40 to +100°C
- DIN rail mounting point
- Wall thickness of 3 mm



ENGLISH

### Specifications:

|                     |                          |
|---------------------|--------------------------|
| Body Material       | Die Cast Aluminium Alloy |
| Colour              | Natural                  |
| External Dimensions | 98 x 64 x 34 mm          |
| External Height     | 34 mm                    |
| External Length     | 98 mm                    |
| External Width      | 64 mm                    |
| Flanged             | No                       |
| Gasket Material     | Neoprene                 |
| IP Rating           | IP66                     |
| Lid Colour          | Silver Grey              |
| Shielded            | No                       |
| Finish              | Unpainted                |