24W US Wall Plug Adapter multicomp PRO

RoHS Compliant



Features

- USA Plug Top
- · DOE Level VI Efficiency
- · Overcurrent Protection
- Short Circuit Protection
- 1 Year Warranty
- UL62368 Approved


Model		MP011402	MP011404
Output	DC Voltage	12V DC	24V DC
	Rated Current	2amp	1amp
	Current Range	0amp to 2amp	0amp to 1amp
	Rated Power	24 Watt	
	Ripple & Noise	240m Vp-p max	
	Output Regulation	±5%	
	Output Connector	2.1mm × 5.5mm × 12mm C+ve	
Input	Voltage Range	90V AC to 264V AC	
	Frequency Range	47Hz to 63Hz	
	Input Current	0.8amp Max	
	Inrush Current	60mA Max	
	Standby Power	0.1W Max	
	Leakage Current	0.25amp Max	
	Input Connector	USA	
Environment	Operating Temp	0°C to 40°C	
	Cooling	Convection	
	Temperature Coefficient	0.05%/°C	
	Humidity	5 to 95%RH(non-condensing)	
	Storage Temp	-20°C to +80%°C	
Safety & EMC	Safety Standards	UL62368-1	
	EMC Emissions	FCC Part 15 Class B	

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



24W US Wall Plug Adapter multicomp PRO

Mechanical Specification



Dimensions: Millimetres

Part Number Table

Description	Part Number
Wall Plug USB Adapter, US Plug	MP011402
Wall Plug USB Adapter, US Plug	MP011404

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

