


**Datasheet**

**RS PRO M12 Male Straight – RJ45 4 Pin D-Coded Connector, PUR Cable, 2m**

Part No: 2017181




**Technical Specifications:**


Rated Operational Voltage	60 V	
Current Rating	1.5 A	
Insulation Resistance	≥100 MΩ	
Temperature Range	-25° ... +85°C	
Coding	D-Coded	
Degree of Protection	M12 = IP67 / RJ45 = IP20	
	<b>M12</b>	<b>RJ45</b>
Grip Material	PU	PBT
Contact	Cu-Zn	Phosphor Bronze
Contact Plating	Gold Flash	Gold Flash
Contact Carrier	Nylon 66	PBT
O-ring	Neoprene	
Coupling Nut	Brass Nickel-Plated	Brass Nickel-Plated

## Cable Specifications:

Cable Length-L	2 m
Cable Type	Cat5e PUR (2 x 2 Twisted Pair)
Sheath Colour	Teal
Cross Section of Wire	AWG 24
Cable Dia	6.2 ± 0.3 mm
Core Insulation	PE
Termination	RJ45
Transfer Parameters	CAT5E
Transfer Rate	up to 100 Mbit/s
Shielding Details	Braiding 75% Approx.



## Wiring Diagram:



Quality Standard: IEC 61076-2-101



Type Approved  
Safety  
Regular Production  
Surveillance



www.tuv.com  
ID 1111210483

