

Datasheet
 Stock No:1706988

RS Pro
N STRAIGHT BULKHEAD JACK RECEPTACLE (POST CONTACT)

8.3(.327) MAX. PANEL

5/8"-24UNEF

23.4(.921)

FLATS 13.4(.528)

5.4(.213)

36.4±0.5(.1433±.020)

19.0(.748) HEX.

3.11 (.122)

13.5 MIN.

(.531)

13.5 MIN.

(.625) ±0.15.9 MIN.

φ20.5(.807)

φ22(.866) REF.

MOUNTING HOLE
 SCALE 2:1

APPROVED by _____ DATE: _____

1.0 ELECTRICAL
 1.1 FREQUENCY RANGE: DC-11 GHz
 1.2 NOMINAL IMPEDANCE: 50 OHM
 1.3 VOLTAGE RATING: 1000 VOLTS MAX.
 1.4 VSWR: 1.1 MAX @6GHz
 1.3 MAX @11GHz

2.0 MATERIALS
 2.1 BODIES: BRASS PER JIS-C3604
 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300
 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

3.0 FINISHES AND OTHERS
 3.1 SEE BELOW TABLE FOR DETAILS.

4.0 MECHANICAL
 4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-348A

5.0 ENVIRONMENTAL
 5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
6	WASHER	BRASS	1	WHITE BRONZE 80µ MIN.
5	NUT	BRASS	1	WHITE BRONZE 80µ MIN.
4	O-RING	SILICONE	1	BLACK
3	INSULATION	TEFLON	1	NONE
2	BODY	BRASS	1	WHITE BRONZE 80µ MIN.
1	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 3µ MIN.

DESCRIPTION	TOLERANCE	品名	DATE	REV
N STRAIGHT BULKHEAD JACK RECEPTACLE (POST CONTACT)	±0.2	40610209000001	01.04.18	A-0
	±0.1	ROHS COMPLIANT (500)		
	±0.05	DWG. NO. 61-0021-Z		
	±5°	UNIT mm(in)		
		SCALE		
		比例		
		3:1		

DRAWN	TITLE	DATE	REV
Jackie	ROHS COMPLIANT (500)	01.04.18	A-0
Jackie	ROHS COMPLIANT (500)	01.04.18	A-0