



### Main

|                           |         |
|---------------------------|---------|
| Range                     | Vivace  |
| Product or component type | Switch  |
| Device short name         | KB31    |
| Device application        | Control |
| Switch function           | 1-way   |

### Complementary

|                                |   |
|--------------------------------|---|
| Device presentation            | Complete mechanism  |
| Actuator                       | Rocker  |
| Number of gangs                | 1 gang  |
| Colour tint                    | Aluminium silver  |
| Material                       | Polycarbonate: grid plate<br>Polycarbonate: surround<br>Polycarbonate: base |
| Projecting depth               | 8 mm  |
| Device mounting                | Flush   |
| Mounting support               | Wall mounted  |
| Fixing mode                    | By screw M3.5   |
| Fixing center                  | 60.3 mm   |
| Embedding depth                | 35 mm   |
| Rated current                  | 16 AX at 250 V AC, inductive<br>16 AX at 250 V AC, fluorescent              |
| [Ue] rated operational voltage | 250 V AC  |
| Network frequency              | 50 Hz   |
| Contacts material              | Brass and phosphor bronze   |
| Connections - terminals        | Pillar terminal   |
| Terminal identifier            | L1<br>L2<br>COM   |
| Tightening torque              | 0.4 N.m   |
| Clamping connection capacity   | 2.5 mm <sup>2</sup>   |
| Width                          | 87 mm   |
| Height                         | 87 mm   |

### Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | SS 227<br>MS IEC 60669-1<br>IEC 60669-1 |
| Ambient air temperature for operation | -5...40 °C                              |
| Relative humidity                     | 0...95 %                                |
| Environmental characteristic          | Indoor use                              |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 3.8 cm  |
| Package 1 Width              | 8.6 cm  |
| Package 1 Length             | 8.6 cm  |
| Package 1 Weight             | 63 g    |
| Unit Type of Package 2       | BB1     |
| Number of Units in Package 2 | 8       |
| Package 2 Height             | 9.5 cm  |
| Package 2 Width              | 15 cm   |
| Package 2 Length             | 19 cm   |
| Package 2 Weight             | 576 g   |
| Unit Type of Package 3       | CAR     |
| Number of Units in Package 3 | 80      |
| Package 3 Height             | 21 cm   |
| Package 3 Width              | 31.5 cm |
| Package 3 Length             | 50 cm   |
| Package 3 Weight             | 5.37 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |