



Main

Range of product	TeSys GV5
Range	TeSys
Device short name	GV5P
Product name	TeSys GV5 TeSys Giga
Product or component type	Motor circuit breaker
Device application	Motor protection
Trip unit technology	Electronic

Complementary

Poles description	3P
Utilisation category	Category A conforming to IEC 60947-2
Motor power kW	55...75 kW at 400/415 V AC 50/60 Hz 75...90 kW at 500 V AC 50/60 Hz 90...110 kW at 660/690 V AC 50/60 Hz
Breaking capacity	36 kA Icu at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 30 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 8 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service short-circuit breaking capacity	100 % at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 500 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
Control type	Direct rotary handle
[In] rated current	150 A at 65 °C
Magnetic tripping current	2250 A
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-2
[Ith] conventional free air thermal current	150 A conforming to IEC 60947-4-1
[Uimp] rated impulse withstand voltage	8 kV
Power dissipation per pole	9.2 W
Mechanical durability	40000 cycles
Electrical durability	20000 cycles for AC-3 at 400/415 V In
Maximum operating rate	25 cyc/h
Rated duty	Continuous
Connection pitch	35 mm without spreaders
Connections - terminals	Bars Lugs
Tightening torque	15 N.m M8 screw type
Mechanical robustness	Vibrations: +/- 1 mm 2...13.2 Hz conforming to IEC 60068-2-6 Vibrations: 0.7 gn 13.2...100 Hz conforming to IEC 60068-2-6
Phase failure sensitivity	Yes conforming to IEC 60947-4-1
Height	161 mm
Width	105 mm
Depth	155 mm
Product weight	2.4 kg
Colour	Anthracite (RAL 7016)
Suitability for isolation	Yes conforming to EN/IEC 60947-2

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	IECEE CB Scheme EAC (pending)
Climatic withstand	Conforming to IACS E10
IK degree of protection	IK07 conforming to IEC 62262
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for storage	-50...85 °C
Fire resistance	960 °C conforming to IEC 60695-2-11
Operating altitude	5000 m
Ambient air temperature for operation	-25...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.8 cm
Package 1 Width	17.0 cm
Package 1 Length	19.1 cm
Package 1 Weight	2.4 kg
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	13.4 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------