

FEATURES

- Material : UL approved Nylon 66, flammability rating 94V-2.
- More effective in marker assembly. It can be applied after completing of terminal assembly to the wire.
- not easy to trans figure and beautiful, clear printing and longer lasting (not fade easily).
- Strip off from the cutting point easily when used. Continuously SM type cable markers is string type and each one is connected.

RS PRO Cable Marker

RS Stock No.: 2153051, 2153052, 2153053, 2153054, 2153056



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

- Material: UL approved Nylon 66 , flammability rating 94V-2.
- More effective in marker assembly. It can be applied after completing of terminal assembly to the wire.
- not easy to trans figure and beautiful, clear printing and longer lasting (not fade easily).
- Strip off from the cutting point easily when used. Continuously SM type cable markers is string type and each one is connected.

General Specifications

Series	Cable Marker
Type	
Material	Nylon 66, 94V2
Finish	
Application	
Resistant To	
UV Resistant	No
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	85°C
Fire Behaviour	Self-Extinguishing
Quantity	1200

Mechanical Specifications

Length	2.9mm / 2.8mm
Suitable Wire	0.5~1.5 sq / 1.5~2.5 sq
Suitable Range(I.D.)	2.2~2.8 / 3.0~3.6

Approvals

Declarations	
Standards Met	RoHS, HF, SVHC

Similar Products

Stock No.	Brand	Product Name	Colour	Material	Tensile strength
812-1240	RS	Cable Marker	Yellow	Nylon66	
812-1203	RS	Cable Marker	Color assortment	Nyloy66	



Unit: mm

RS Article(will be replayed RS new article no.)	KSS Item No.	Suitable Wire		Suitable Range	L	Std. Markings	Color	Packing
		sq	AWG	I.D.				
2995348	SM1-0BK	0.5 ~ 1.5	20 ~ 18	2.2 ~ 2.8	2.9	0	Black	1200 pcs / Box
2985650	SM1-1BN6	0.5 ~ 1.5	20 ~ 18	2.2 ~ 2.8	2.9	1	Brown	
2985672	SM1-2RD	0.5 ~ 1.5	20 ~ 18	2.2 ~ 2.8	2.9	2	Red	
2985688	SM1-3OE	0.5 ~ 1.5	20 ~ 18	2.2 ~ 2.8	2.9	3	Orange	
2986085	SM2-1BN6	1.5 ~ 2.5	16 ~ 14	3.0 ~ 3.6	2.8	1	Brown	