

serie/series:

INDUSTRIAL

PR

COMPRESSORI INDUSTRIALI - BISTADIO TRASMISSIONE A CINGHIA - LUBRIFICATI
 OIL-LUBRICATED - DOUBLE-STAGE INDUSTRIAL COMPRESSORS WITH BELT DRIVE
 COMPRESSEURS INDUSTRIELS - DEUX STADE ENTRAÎNEMENT PAR COURROIE - LUBRIFIÉS
 HOCHPROFESIONELLE ZWEISTUFIG VERDICHTER RIEMENANTRIEB - MIT SCHMIERSYSTEM
 COMPRESORES INDUSTRIALES - DE DOS ETAPAS TRANSMISIÓN DE CORREA - LUBRICADOS
 COMPRESSORI A BASSI REGIMI DI ROTAZIONE DA 850 A 1000 RPM(G/MIN)
 COMPRESSORS AT LOW SPEEDS OF ROTATION FROM 850 TO 1000 RPM (G/MIN)
 COMPRESSEURS À MARCHE LENTE DE ROTATION DE 850 À 1000 RPM (G / MIN)
 COMPRESORES A BAJAS VELOCIDADES DE ROTACIÓN DE 850 A 1000 RPM (G / MIN)
 KOMPRESSOREN BEI NIEDRIGEN DREHZAHLEN VON 850 BIS 1000 RPM (G / MIN)

SERIE/SERIES PR



CARATTERISTICHE TECNICHE - TECHNICAL DATA SERIE/SERIES PR

COD	TYPE	Liters	Cil	lt/min	CFM	m³/h	bar	psi	Hp/Cv	kW	Volt/ph	r p m	Kg	Lbs	A x B x h
16007	PR 270/5.5T	270 C	2B	650	23	39	10	143	5,5	4	400/3	900	170	374	155x57x118
16008	PR 270/7.5T	270 C	2B	830	30	49,8	10	143	7,5	5,5	400/3	1000	185	407	155x57x118
16009	PR 270/10T	270 C	2B	1210	42,7	72,6	10	143	10	7,5	400/3	950	215	473	155x57x118
17007	PR 500/5.5T	500 C	2B	650	23	39	10	143	5,5	4	400/3	900	215	473	203x70x131
17008	PR 500/7.5T	500 C	2B	830	30	49,8	10	143	7,5	5,5	400/3	1000	215	473	203x70x131
17009	PR 500/10T	500 C	2B	1210	42,7	72,6	10	143	10	7,5	400/3	950	266	585	203x70x131

SERIE/SERIES PR



CARATTERISTICHE TECNICHE - TECHNICAL DATA SERIE/SERIES PR

COD	TYPE	Liters	Cil	lt/min	CFM	m³/h	bar	psi	Hp/Cv	kW	Volt/ph	r p m	Kg	Lbs	A x B x h
16007.1	PR 270/5.5TF	270 F	2B	650	23	39	10	143	5,5	4	400/3	900	170	374	155x57x118
16008.1	PR 270/7.5TF	270 F	2B	830	30	49,8	10	143	7,5	5,5	400/3	1000	185	407	155x57x118
16008.1.1	PR 270/7.5TF ST	270 F	2B	830	30	49,8	10	143	7,5	5,5	400/3	1000	200	440	155x57x118
16009.1	PR 270/10TF	270 F	2B	1210	42,7	72,6	10	143	10	7,5	400/3	950	215	473	155x57x118
16009.1.1	PR 270/10TF ST	270 F	2B	1210	42,7	72,6	10	143	10	7,5	400/3	950	230	506	155x57x118
17007.1	PR 500/5.5TF	500 F	2B	650	23	39	10	143	5,5	4	400/3	900	215	473	203x70x131
17008.1	PR 500/7.5TF	500 F	2B	830	30	49,8	10	143	7,5	5,5	400/3	1000	215	473	203x70x131
17008.1.1	PR 500/7.5TF ST	500 F	2B	830	30	49,8	10	143	7,5	5,5	400/3	1000	230	506	203x70x131
17009.1	PR 500/10TF	500 F	2B	1210	42,7	72,6	10	143	10	7,5	400/3	950	266	585	203x70x131
17009.1.1	PR 500/10TF ST	500 F	2B	1210	42,7	72,6	10	143	10	7,5	400/3	950	281	618	203x70x131
17010.1.1	PR 500/15TF ST	500 F	2B	1390	48,6	83,4	10	143	15	11	400/3	1100	291	640	203x70x131
18009.1.1	PR 900/10TF ST	900 F	2B	1210	42,7	72,6	10	143	10	7,5	400/3	950	386	849	212x85x161