

## Datasheet

# RS Pro Flush Indicator, 8mm Mounting Hole Size, Hyper Bright Yellow LED, Faston, Solder Lug Termination, 24 V dc

RS Stock No: **913-8719**



## Product Details

RS Pro flush indicator with 8 mm mounting hole, features hyper bright yellow LEDs for panel mount applications. With an IP67 rating, it is suitable for most environments including outdoor applications. This indicator accommodates a lamp size of 5 mm and offers extended short body solder lug/faston termination. It has a voltage rating of 24 V dc. The indicator has a wide operating temperature range of -40 to +85°C, further increasing the potential applications they may be used for. The 5 mm LED requires an 8 mm panel cut-out and is supplied with a fixing nut and spring washer. It offers a wide selection of voltage ratings, bezel finishes and bezel styles.

## Features and Benefits

- 8 mm panel mounting LED indicator
- Coloured diffused epoxy lens or water clear super bright LEDs
- Prominent, recessed, chamfer and flush bezel styles
- Sealed to IP67
- Operating temperature range: -40 to +85°C

**Specifications:**

|                      |  |
|----------------------|--|
| Bezel Colour         | Bright Chrome                          |
| Bezel Style          | Flush                                  |
| Current Rating       | 20 mA                                  |
| Intensity            | 250 mcd                                |
| IP Rating            | IP67                                   |
| Lamp Size            | 5 mm                                   |
| Lamp Type            | LED                                    |
| Length               | 22.6 mm                                |
| Light Output Colour  | Yellow                                 |
| Mounting Hole Size   | 8 mm                                   |
| Termination Type     | Extended Short Body Solder Lug/Fastons |
| Type                 | Panel Mount                            |
| Voltage Rating       | 24 V dc                                |
| Temperature Rating   | -40 to +85°C                           |
| Type of Illumination | Fixed Light                            |
| LED Colour           | Hyper Bright Yellow                    |



**ENGLISH**

| TECHNICAL SPECIFICATIONS |                                   |  |
|--------------------------|-----------------------------------|--|
| Voltage                  | Operating Voltage<br>(Min to Max) | Operating Current<br>(Typical All Types) |
| 02 (No Resistor)         | 1.8 to 3.3VDC                     | 20mA max*                                |
| 6VDC                     | 5.4 to 6.6VDC                     | 20mA                                     |
| 12VDC                    | 10.8 to 13.2VDC                   | 20mA                                     |
| 24VDC                    | 21.6 to 26.4VDC                   | 20mA                                     |
| 28VDC                    | 25.2 to 30.8VDC                   | 20mA                                     |
| 110VAC                   | 99 to 121VAC                      | 6mA                                      |
| 220VAC                   | 207 to 253VAC                     | 3mA                                      |

|  |
|--|
| <b>Max Reverse Voltage:</b> 5V                               |
| <b>Viewing Angle:</b> 30–100° (dependant on model)           |
| <b>Life Expectancy:</b> 100,000 hours                        |
| <b>Temperature Range:</b> –40 to +85°C (operating & storage) |
| <b>Torque:</b> 20 to 25cNm                                   |

PANEL CUTOUT

M8 x 0,75 THREAD

| Standard LED Intensity                 | Prominent and Recessed | Flush      | Forward Voltage |
|--|------------------------|------------|-----------------|
| HE Red                                 | 80mcd                  | 8mcd       | 2.0V            |
| Green                                  | 60mcd                  | 6mcd       | 2.2V            |
| Yellow                                 | 50mcd                  | 6mcd       | 2.1V            |
| Blue                                   | 1600mcd                | 50mcd      | 3.3V            |
| White                                  | 1600mcd                | 500mcd     | 3.3V            |
| Orange                                 | 60mcd                  | 110mcd     | 2.2V            |
| Bi-color (Typical) (Red/Green)         | 14/30mcd               | 15/10mcd   | 2.0V/2.2V       |
| Tri-color (Typical) (Red/Green/Yellow) | 60/15/13mcd            | 15/10/6mcd | 2.0V/2.2V/2.1V  |

Bi-color - The color is changed by reversing the polarity of the supply voltage.

Tri-color - The indicator has red and green LEDs, when both connected yellow is produced.

| Super Bright LED | Prominent and Recessed | Flush    | Forward Voltage |
|------------------|------------------------|----------|-----------------|
| HE Red           | 5,000mcd               | 1,300mcd | 2.2V            |
| Green            | 10,000mcd              | 1,200mcd | 3.3V            |
| Yellow           | 4,000mcd               | 350mcd   | 2.0V            |
| Blue             | 2,200mcd               | 280mcd   | 3.3V            |
| White            | 2,500mcd               | 950mcd   | 3.3V            |
| Orange           | 4,000mcd               | 500mcd   | 2.2V            |

| Hyper Bright LED | Prominent and Recessed | Flush  | Forward Voltage |
|------------------|------------------------|--------|-----------------|
| HE Red           | 6,000mcd               | 980mcd | 2.2V            |
| Green            | 1,900mcd               | 300mcd | 3.3V            |
| Yellow           | 1,600mcd               | 250mcd | 2.0V            |
| Orange           | 2,400mcd               | 110mcd | 2.2V            |

Luminous intensity will be reduced with lower operating current.

Note: The operating voltage must not be exceeded by more than 10% as this will result in reduced life expectancy.

The company reserves the right to change specifications without notice.

\* Customer to supply resistor for desired operating current.

Luminous intensity is measured at 20mA on a discrete LED unless otherwise stated.

Luminous intensities and color shades of white LEDs may vary within a batch.

LED characteristics are dependent upon environmental conditions. Therefore published data should be considered nominal.

Technical Drawings  
FLUSH BEZEL

