



LPS® MAX PreSolve®

Industrial Orange Degreaser



FEATURES

- Removes grime with MAX speed
- Effectively dissolves tars, asphalt, mastics, and adhesive residues
- Low residue
- Fast acting, deep penetration
- Safe on all metals and most plastics
- No chlorinated solvents
- Controlled evaporation
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip
- Locking flip straw actuator

APPLICATIONS

| | |
|------------------------------|-----------------------|
| • Air Compressors | • Forklifts |
| • Alternators | • Gears |
| • Bearings | • Heavy Equipment |
| • Chains & Cable Connections | • Power and Air Tools |
| • Cranes | • Printing Presses |
| • Engines | • Pulleys |

SPECIFICATIONS AND APPROVALS

- NSF International, C1
- Pratt & Whitney Canada MMC 21530

AVAILABLE PRODUCTS

| Part No. | Net Contents | Container Type | Units/Case | Case Weight |
|----------|---------------------------|----------------|------------|-------------|
| 91420 | 15 wt oz / 425 g / 523 mL | aerosol | 12 | 15 lbs |

PROPERTIES

| | |
|-----------------------------|---|
| Appearance / Physical State | Gas |
| Color | Clear, Off-white |
| Odor | Orange |
| Flash Point | 104.0°F (40.0°C) Tag Closed Cup |
| Evaporation Rate | > 0.1 BuAc |
| Vapor Pressure | < 5 mm Hg @ 20°C |
| Vapor Density | > 1 (air = 1) |
| Auto-Ignition Temperature | > 392°F (> 200°C) |
| Viscosity | < 3 cSt @ 25°C |
| Percent Volatile | 100% |
| Specific Gravity | 0.82-0.86 @ 20°C |
| VOC Content | 97% per US State and Federal Consumer Product Regulations |
| Prop 65 Warning | No |

HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

STORAGE

Content under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Dispose of contents/container in accordance with local/regional/national/international regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved