

Features

- 2 port solenoid valve
- 3/8in push fit connections
- NC (normally closed) default valve position
- Maximum operating temperature of +60°C
- Maximum working pressure of 10 bar
- Solenoid operation
- Orifice diameter of 2.6 mm
- Suitable for potable water
- Supply voltage of 230 V AC/DC
- Power of 5W
- Duty cycle of 3 min on/ 5 min off
- Class F coil insulation

RS PRO Solenoid Valves

RS Stock No.: 190-4138



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

A 2-port solenoid valve designed to release or to shut off the supply of water to hoses and sprinklers. Featuring a high maximum operating pressure of 10 bar enabling the reliable flow control over long lengths of piping.

General Specifications

AMBIENT TEMPERATURE:	60°C Max
MEDIUM:	Potable water 90° Max
DUTY CYCLE 100%:	Tu 60°C, Tm 25°C
DUTY CYCLE:	3min ON / 5min Off - Tu 60°C, Tm 90°C
OPERATING PRESSURE:	0.2 - 10 Bar

Mechanical Specifications

TERMINALS:	6mm x 0.8mm Male tab terminals (x2)
------------	-------------------------------------

Electrical Specifications

VOLTAGE:	230V
FREQUENCY:	AC/DC
POWER DRAW:	5w
COIL INSULATION:	CLASS F (140°C OPERATING TEMPERATURE)