

## Datasheet

### 1000 R 1/8 Male 15 bar Pneumatic Straight Threaded-to-Tube Adapter, Push In 6 mm 6mm Male R Push In 1/8in

RS Stock number [299-3932](#)



### Product Details

**Straight Adaptor - Male Tapered/Parallel**

RS, Professionally Approved Products, gives you professional quality parts across all product categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.

**Threaded, Tube-to-Tube & Adaptors**

**Threaded Tube-to-Tube & Adaptors**

The push-on and screw collar design of these fittings makes them secure and suitable for instrumentation, vacuum and general purpose applications, and they can be used with nylon or polyurethane tubing.

Operating Temperature Range -18 to +70°C

Operating Pressure of -1 to 15 bar

Add product to Compare

### Specifications

[Find alternatives](#)

To find a similar product, based on selected attributes, click the green button

Manufacturer Series	1000
Maximum Operating Pressure	15 bar
Maximum Operating Temperature	+70°C
Minimum Operating Temperature	-18°C
Threaded Connection	R 1/8 Male
Threaded Connection - Gender	Male
Threaded Connection - Thread Size	1/8in
Threaded Connection - Thread Standard	R
Tube Connection	Push In 6 mm
Tube Connection - Tube Size	6mm
Tube Connection - Type	Push In