



### Overview

Lead time	Usually in Stock
-----------	------------------



### Main

Provided equipment	Temperature sensor User manual USB cable
--------------------	--

### Physical

Height	3.8 cm
Width	12.1 cm
Depth	11.4 cm
Net weight	0.09 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

### Conformance

Standards	EN 55022 class A EN 55024 ICES-003
Product certifications	AS/NZS 3548 (C-Tick) class A[RETURN]FCC part 15 class A[RETURN]GOST[RETURN]VCCI class A

### Environmental

Ambient air temperature for operation	0...45 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-5...45 °C
Storage altitude	0.00...15240.00 m
Storage Relative Humidity	0...95 %

### Communications & Management

Authentication	Radius
----------------	--------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.200 cm
Package 1 Width	16.400 cm
Package 1 Length	24.000 cm
Package 1 Weight	405.000 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------