




ENGLISH

Datasheet

2 Output Toroidal Transformer, 50VA, 15 V ac

RS Stock number [671-9094](#)

Open Style, with leads, 2x115V Primary, 50VA



RS Code No.	RS Part No.	Full Load Vsec [V]	Rated Current per Sec [A]	No Load Vsec [V]	DC resistance [Ohms] @ 25° C
671-9088	81574-P2S2	2x6	4.167	2 x 6.82	2 x 0.0978
671-9097	81575-P2S2	2x9	2.778	2 x 10.29	2 x 0.2029
671-9090	81576-P2S2	2x12	2.083	2 x 13.63	2 x 0.3783
671-9094	81577-P2S2	2x15	1.667	2 x 17.10	2 x 0.6079
671-9104	81578-P2S2	2x18	1.389	2 x 20.57	2 x 0.8205
671-9107	81579-P2S2	2x25	1.000	2 x 28.50	2 x 1.6018
671-9101	81580-P2S2	2x55	0.455	2 x 62.70	2 x 7.8847

Primary Winding

Input Voltage : 2 x 115V±10% @ 50/60Hz
DC Resistance @25°C = 2 x 25 Ohms (approx)
Magnetising Current @ 115V = 150.0mA (approx)
Magnetising Current @ 126.5V = 350.0mA (approx)

Losses

Iron Losses 4.50 Watts (approx)
Copper Losses 8.90 Watts (approx)

Temperature Class

Winding Wire (Primary & Secondary). Class H (180° C)
Insulation between input and output. Class B (130° C)
Connection lead insulation. Class A (105° C)

Standards

Designed,manufactured and tested according to the requirements of:
EN61558 Class II, Non-Short-Circuit Proof
VDE0570 Class II
IEC61558 Class II
UL506

Physical Data

Approximation Dimension Diameter 80mm*
Height 33mm
Approximate weight * Measured away from leadout bulge, allow extra 4mm at leads
0.74 Kg

Terminations

Primary Flexible equipment wire, 105°C PVC, 7/0.20 (0.22mm²)
Double Insulated over entire length with PVC sleeves
150mm Long, with 10mm stripped ends.
Secondary Solid copper conductors (extension of winding wire)
insulated over their entire length with PVC tubing
150mm Long, with 10mm tinned ends.