

## **FEATURES**

- Quick connection and disconnection
- Large range to comply food norms
- Silicon free
- Operating temperature range is from - 15 °C to + 190 °C

# RS PRO STRAIGHT MALE ADAPTOR (PARALLEL) -FOOD GRADE

RS Stock No.: 2312751



RS PROfessionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

# **Pneumatic Quick Connect Couplings**



### **Product Description**

The RS PRO straight male adaptor (parallel) works in - 0.99 bar to 20 bar pressure range. It is mainly used in dairy, coffee machine, vending, food & beverage, medical, vacuum applications. It is available in brass with Food Grade coating. In combination with FEP tubes, it is the most demanded solution for the Food & Beverage market. Beacause of the special coating it can be used also in agressive environment.

RoHS and REACH compliant.

#### **General Specifications**

Material	Nickel Plated Brass		
Applications	Lubrication System, Cooling System, Pneumatic		
	Machinery Equipment		

#### **Mechanical Specifications**

Connection Type	Threaded, Tube 12mm Male			
Tube Connection Size				
Coupling Gender				
Threaded Connection	3/8 in Male			
Thread Size	3/8in			
Hose Barb Connection	12mm 20mm			
Mounting Hole Diameter				
Wrench Size1	20			
Wrench Size2	8			
Length	34mm			




# **Operation Environment Specifications**

Minimum Operating Temperature	-15°C
Maximum Operating Temperature	190°C

## **Similar Products**

Parameters	2312744	2312745
Brand	RS PRO	RS PRO
Connection Type	Threaded, Tube	Threaded, Tube
Hose Barb Connection	4mm	6mm
Coupling Gender	Male	Male
Threaded Connection	1/8 in Male	1/8 in Male
Thread Size	1/8in	1/8in
Hose Barb Connection	4mm	6mm
Mounting Hole Diameter	13mm	13mm
Wrench Size1	10	13
Wrench Size2	2	4
Length	21mm	23.5mm





Tube	Α	В	С	L	CH1	CH2	Pack.
12	3/8	8.1	20	34	20	8	10