



Modular Flat Telephone Cable

Description

Stranded TACW, 4 core, PVC insulation, PVC sheath

Application

Telephone handset cord or line cord

Construction

Conductor

Material : Stranded TACW
Stranding : 7 / 0.15mm

Insulation

Material : PVC
Nominal Inner Diameter : 0.95mm
Colour : A : White, B : Green, C : Blue and D : Red

Sheath

Material : PVC
Nominal Outer Diameter : 2.9mm × 5mm
Colour : Grey

Physical Properties

Min. Bend Radius : 29 mm
Operating Temperature : -15°C to 70°C

Electrical Properties

Nominal DC Resistance : 166Ω / km
Voltage Test : Core to core : 1,000V AC / 1 minute

Diagram



Part Number Table

Description	Part Number
Cable, CW1311, 4 Core, 100m	TEM0037-2009

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.