

LE2D12N7

Enclosed reversing starter, TeSys LE, 12A, 415V AC coil, including 2 LC1D, pushbutton and rotary switch



Main

| | |
|--|--|
| Range | TeSys |
| Product name | TeSys LE |
| Device short name | LE2D |
| Product or component type | Enclosed DOL reversing starter |
| Device application | Standard |
| Utilisation category | AC-3 |
| Device composition | Thermal overload relay ordered separately Reversing contactor |
| Motor power kW | 3 KW at 220/230 V AC 50/60 Hz 7.5 KW at 500 V AC 50/60 Hz 7.5 KW at 660/690 V AC 50/60 Hz 5.5 KW at 380/400 V AC 50/60 Hz 5.5 KW at 415 V AC 50/60 Hz 5.5 kW at 440 V AC 50/60 Hz |
| [I _{th}] Conventional free air thermal current | 12 A |
| [U _c] control circuit voltage | 415 V AC 50/60 Hz |
| Control type | Push-button stop/reset red O Selector switch 2 positions start I-II |

Complementary

| | |
|--------------------|--|
| Cable entry number | 2 ISO20 top 2 ISO25 top 2 ISO20 bottom 2 ISO25 bottom |
| Width | 101 mm |
| Height | 201 mm |
| Depth | 160 mm |
| Net weight | 2.1 kg |

Environment

| | |
|---------------------------------------|------------------------------|
| Material | Polycarbonate |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529 |
| Standards | IEC 60947-4-1 |
| Ambient air temperature for operation | -5...40 °C |
| Environmental characteristic | Standard environment |
| Product certifications | UKCA |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 26.0 cm |
| Package 1 Width | 29.0 cm |
| Package 1 Length | 40.0 cm |
| Package 1 Weight | 2.1 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|