


GS1AM101

Auxiliary contacts, TeSys GS, 1 NC, early break, front mounting, for GS2 with front/side handle



Main

Range of product	TeSys
Device short name	GS1AM
Product or component type	Auxiliary contact
Contact application	O, I and test position signalling
Range compatibility	TeSys (TeSys GS) fuse-switch disconnecter FuPact (FuPact GS) fuse-switch disconnecter
Contacts type and composition	1 NC
Contact operation	Early-break
[I _{th}] conventional free air thermal current	10 A (at 40 °C)
[I _e] rated operational current	6 A at 120 V AC-15 3 A at 240 V AC-15 1.8 A at 400 V AC-15 1.5 A at 480 V AC-15 2.8 A at 24 V DC-13 1.4 A at 48 V DC-13 0.55 A at 125 V DC-13 0.27 A at 250 V DC-13 0.15 A at 400 V DC-13

Complementary

Mechanical durability	5 Mcycles
Electrical durability	1 Mcycles AC-15
Switch rated current	30 A 32 A 50 A 60 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A 600 A 630 A 800 A 1250 A
Fuse type	NFC DIN BS CC J
Type of operating handle	External frontal External right side External left side
Mounting location	Front face
Net weight	0.015 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	6 cm
Package 1 Length	8 cm
Package 1 Weight	13 g
Unit Type of Package 2	S01
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	15 cm
Package 2 Length	40 cm
Package 2 Weight	312 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------