

Datasheet

RS PRO Type B BSPP Female Coupler x BSPT Male End



Image representative of range

Technical Specifications:

| Specifications | |
|--------------------|-------------------|
| Gasket | Buna-N Nitrile |
| Temperature Rating | -40° C to +100° C |

Features & Benefits:

- **Manufactured to interchange with all products produced to MIL-C-27487F**
- **BSP male threads to BS21 (Taper)**
- **BSP female threads to BS2779 (Parallel)**

Pressure Ratings:

- **Recommendations based on the use of mating fittings at ambient temperature 20°C with standard Nitrile seals installed.**

| RS Article | Size | Material | Working Pressure |
|------------|--------|-----------------|------------------|
| 362-6683 | 1" | Aluminium | 17.2 bar |
| 382-5666 | 1" | Polypropylene | 7 bar |
| 307-184 | 1" | Stainless Steel | 17.2 bar |
| 362-6699 | 1.1/2" | Aluminium | 17.2 bar |
| 382-5672 | 1.1/2" | Polypropylene | 7 bar |
| 307-190 | 1.1/2" | Stainless Steel | 17.2 bar |
| 362-6706 | 2" | Aluminium | 17.2 bar |
| 382-5688 | 2" | Polypropylene | 7 bar |
| 307-207 | 2" | Stainless Steel | 17.2 bar |