Product data sheet Characteristics

EPDU1216S

Easy Rack PDU, Switched, 0U, 3 Phase, 11kW, 230V, 16A, 21 C13 and 6 C19 outlets, IEC60309 3P + N + PE inlet



Overview

Lead time	Usually in Stock

Main

Colour	Black
PDU type	Switched
Number of cables	1

Complementary

o o p. o		
Main Input Voltage	400 V 3 phases	
Height	1794 mm	
Width	55 mm	
Main Output Voltage	230 V	
Depth	62 mm	
Net weight	6.2 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Connection Type	IEC 60309 16 A 3P + N + PE	
Mounting position	Vertical	
Input current limits	16 mA	
Load capacity	11 kW	
Network frequency	50/60 Hz	
Plug standard	IEC 60309	
Number of power socket outlets	21 IEC 60320 C13 6 IEC 60320 C19	

Environment

Product certifications	CE[RETURN]EAC[RETURN]RCM[RETURN]TÜV	
Ambient air temperature for operation	-545 °C	
Relative humidity	595 %	
Operating altitude	03000 m	
Ambient air temperature for storage	-2565 °C	
Storage Relative Humidity	595 %	
Storage altitude	015000 m	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.95 cm	
Package 1 Width	16 cm	
Package 1 Length	11 cm	
Package 1 Weight	7.78 kg	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
	•

Contractual warranty