

INDUSTRIAL SCAFFOLDING



320

RBQ SERIES
45 ~ 250 KGS

In Compliance to Building & Construction Safety

Castor 320

Galvanized pressed steel. Double ballrace swivel head
80 ~ 125mm Rig thickness: 2mm
160 ~ 200mm Rig thickness: 3mm

Wheel RBQ

Solid rubber black tire with steel hub & threadguards
Tough load for industrial usage. Safety load at max speed 4 Kph
Hardness: 80± Shore A • Temperature Range: -20°C to +60°C
Hardness: 94± Shore A • Temperature Range: -20°C to +90°C



Perspective view
of total-brake


















Scaffold Castor
with total-brake



RBQ

RBZ

Wheels	profile	 mm	 mm	 mm/inch	 mm	 bush	 TG	 bearing	 kgs
RBQ 075	Convex	75	20	12	31		Yes		40
RBQ 080	Convex	80	24	12	41		Yes		45
RBQ 100	Convex	100	27	12	41		Yes		65
RBQ 125	Convex	125	34	12	41		Yes		95
RBQ 160	Convex	160	40	20	60		Yes		125
RBQ 200	Convex	200	46	20/1"	60		Yes		195
RBQ 250	Convex	250	50	1"	56		No		250

Remarks: Single wheels are supplied without threadguards and axle materials.

RBZ 200	Convex	200	46	15	25		No		195
----------------	--------	-----	----	----	----	--	----	---	-----