

WASHERS

Nylon Washers



Selection Table		
Gland Size Metric	Gland Size NPT *	Thickness
M16	½"	1.5
M20	¾"	1.5
M25	1"	1.5
M32	1 ¼"	1.5
M40	1 ½"	1.5
M50	2"	1.5
M63	2 ½"	1.5
M75	3"	1.5
M80	3 ½"	1.5
M90	4"	1.5
M100	4 ½"	1.5
M110	5"	1.5
M115	6"	1.5
M120	6"	1.5
M130	6"	1.5

Note: All dimensions are in millimetres except where * denotes dimensions in inches.

Ordering Example:	
Product	Thread Size
Nylon Washer	M25



General Information

- For use on cable gland entry threads.
- To maintain ingress protection rating of the enclosure.
- Retaining "pips" make washer captive on metric cable gland entry thread.
- Sealing washer for PG thread sizes available.

Certification Details

- BS EN 60529.
- ISO 60079-0, ISO 60079-7.
- -60°C / +130°C.
- IP66/67/68/69.

SERRATED WASHER

Stainless Steel



Selection Table		
Gland Size Metric	Gland Size NPT *	Thickness
M16	½"	1.5
M20	¾"	1.5
M25	1"	1.5
M32	1 ¼"	1.5
M40	1 ½"	1.5
M50	2"	1.5
M63	2 ½"	1.5
M75	3"	1.5
M80	3 ½"	1.5
M90	4"	1.5
M100	4 ½"	1.5
M110	5"	1.5
M115	6"	1.5
M120	6"	1.5
M130	6"	1.5

Note: All dimensions are in millimetres except where * denotes dimensions in inches.

Ordering Example:			
Product	Thread Size	Product	Thread Size
Serrated Washer	M25	Serrated Washer	1" NPT



General Information

- For use on cable gland entry threads.
- To dampen vibrations of the cable gland / equipment assembly.
- Manufactured in Stainless Steel as standard.