



ENGLISH

Datasheet

Aluminium Electrolytic Capacitor

RS Stock number 711-1911




Specifications:

Item	Performance Characteristics	
Operating Temperature Range	-40 to +105°C	-25 to +105°C
Rated Voltage Range	6.3 to 100 VDC	160 to 450 VDC
Capacitance Tolerance	± 20% (120Hz, +20°C)	
Leakage Current (at 20°C, max.)	I < 0.01 CV or 3 (µA). After 1 minute whichever is greater measured with rated working voltage applied.	I < 0.03 CV or 3 (µA). After 1 minute with rated working voltage applied.
Dissipation Factor (120Hz, 20°C)	Working voltage (VDC)	6.3 10 16 25 35 50 63 100 160 200 250 350 400 450
	D.F (%) Max.	23 20 16 14 12 10 10 10 15 15 16 20 20 20
For capacitance > 1000µ F, add 2% per another 1000µ (+20°C at 120Hz)		

Specifications:

Item	Performance Characteristics														
Low Temperature Characteristics (at 120Hz)	Impedance ratio max.														
	W.V (VDC)	6.3	10	16	25	35	50	63	100	160	200	250	350	400	450
	Z-25°C/+20°C	4	3	2	2	2	2	2	2	3	3	3	5	6	15
Z-40°C/+20°C	9	6	4	4	3	3	3	3	-	-	-	-	-	-	
For capacitance value 1000µF, add 0.5 per another 1000µF for -25°C/+20°C For capacitance value 1000µF, add 1 per another 1000µF for -40°C/+20°C															
Load Life	Test Conditions: Duration time: 2000hrs Ambient temperature: +105°C Applied voltage: Rated DC working voltage After test requirements: +20°C After test requirements: ≤ + 20% of initial measured value Dissipation Factor: ≤ 200% of the initial specified value Leakage Current: ≤ the initial specified value														
Shelf Life	Test Conditions: Duration time: 1000hrs Ambient temperature: +105°C Applied Voltage: None After test requirements at +20°C: Same limits as load life. Pre-treatment for measurements shall be conducted after application of DC working voltage for 30 minutes.														

Diagram of Dimensions:



(Unit: mm)

D	5	6	8	10	13	16	18	22	25
F	2.0	2.5	3.5	5.0	5.0	7.5	7.5	10	12
φd	0.5		0.6			0.8		1.0	

**Features:**

- Used in communication equipment's, switching power supply, etc.
- Safety vent construction design

Ripple Current & Temperature

Temperature (°C)	45	60	70	85	105
Multiplier	2.10	1.90	1.65	1.40	1.00

Ripple Current & Frequency Multipliers

CAP (μF)/Hz	50 (60)	120	400	1K	10K	50 – 100K
CAP ≤ 10	0.8	1.0	1.30	1.45	1.65	1.70
10 < CAP ≤ 100	0.8	1.0	1.23	1.36	1.48	1.53
100 < CAP ≤ 1000	0.8	1.0	1.16	1.25	1.35	1.38
1000 < CAP	0.8	1.0	1.11	1.18	1.25	1.28

Case Size

Ø D x L (mm)

WV (SV) uF	6.3		{8}		10		{13}		16		{20}		25		{32}		35		{44}	
	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple
4.7												→	5x11	27	5x11	29				
6.8												→	5x11	35	5x11	38				
10												→	5x11	38	5x11	40	5x11	42		
22												→	5x11	50	5x11	56	5x11	60	5x11	62
33	5x11	56	5x11	60	5x11	65	5x11	72	5x11	78	5x11	85	5x11	90	5x11	96	5x11	102	5x11	108
47	5x11	68	5x11	72	5x11	80	5x11	84	5x11	90	5x11	100	5x11	105	5x11	110	5x11	115	6.3x11	120
68	5x11	77	5x11	82	5x11	90	5x11	96	5x11	102	5x11	110	6.3x11	120	6.3x11	126	6.3x11	132	6.3x11	138
100	5x11	98	5x11	110	5x11	115	5x11	120	5x11	125	5x11	135	6.3x11	150	6.3x11	156	6.3x11	162	6.3x11	168
220	5x11 6.3x11	160 180	6.3x11	180	6.3x11	200	6.3x11	210	6.3x11	220	6.3x11	230	8x11	240	8x11	250	8x11	260	8x11	270
330	6.3x11	200	6.3x11 8x11	260 280	6.3x11	300	8x11	320	8x11	340	8x11	360	8x11 10x12	350 365	10x12	380	10x12	400	10x12	420
470	6.3x11 8x11	280 310	6.3x11 8x11	300 315	6.3x11	340	8x11 10x12	360 400	8x11	380	8x11 10x12	400 420	8x14 10x12	415 445	10x12	450	10x12	480	10x12	520
560	8x11	320	8x11	330	8x11	360	10x12	400	10x12	420	10x12	440	10x15	460	10x15	480	10x15	500	10x15	540
680	8x11	360	10x12	420	10x12	460	10x12	480	10x12	500	10x12	520	10x15	520	10x15	540	10x15	560	10x15	600
820	8x11	390	10x12	480	10x12	520	10x15	550	10x15	580	10x15	600	10x15	640	10x15	660	10x15	680	10x15	720
1000	8x11	420	10x12 10x15	530 580	10x12	570	8x16 10x17	570 630	10x15	600	10x15	630	10x15 10x17 10x20	740 800 850	10x20	800	10x20	840	10x20	880
1200	10x15	480	10x15	650	10x15	700	10x20	750	10x20	800	10x20	850	10x20	850	10x20	900	10x20	950	10x20	1000
1500	10x15	620	10x17	770	10x17	820	10x20	870	10x20	920	10x20	970	13x21	910	13x21	960	13x21	1010	13x21	1060
2200	10x17 10x20	780 800	10x17 10x20	870 900	10x17	960	13x21 13x26	1020 1060	13x21	1080	13x21	1140	13x21 13x26 16x16	1210 1270 1270	16x26	1300	16x26	1360	16x26	1420
2700	10x20	850	13x21	920	13x21	980	13x21	1040	13x21	1100	13x21	1160	16x26	1330	16x26	1400	16x26	1470	16x26	1540
3300	10x20 13x21	970 1010	10x25 13x21	1110 1160	13x21	1220	13x21 13x26	1240	13x21	1300	13x21	1360	16x26 16x31	1480 1540	16x31	1600	16x31	1660	16x31	1720
4700	10x25 13x21	1160 1200	13x21 13x26	1360 1380	16x26	1480	16x26	1540	16x26	1600	16x26	1660	16x31	1800	16x31	1860	16x31	1920	16x31	1980
5600	13x26	1320	16x26	1510	16x26	1600	16x31	1680	16x31	1760	16x31	1840	16x36	1890	16x36	1980	16x36	2070	16x36	2160
6800	16x26	1470	16x26	1660	16x31	1740	16x31	1820	16x31	1900	16x31	1980	18x36	2040	18x36	2120	18x36	2200	18x36	2280
8200	16x26	1520	16x31	1840	16x36	1920	16x36	1980	16x36	2040	16x36	2100	18x36	2090	18x36	2180	22x42	2270	22x42	2360
10000	16x26 16x31	1690 1740	16x36 18x36	1900 1980	18x36	2060	18x36 18x41	2080	18x36	2140	18x36	2200	22x42	2200	22x42	2280	25x44	2370	25x44	2460
15000	16x36 18x36	2080 2190	18x36	2230	22x40	2300	22x40	2360	22x40	2420	22x40	2480	22x42	2500	-	-	-	-	-	-

Ripple Current(mA,rms)at105□120Hz

Case Size uF	50 {63}		63 {79}		100 {125}		160 {200}		200 {250}		
	WV (SV)	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple
0.1		5x11	1.3	5x11	1.3	5x11	1.3	-	-	-	-
0.22		5x11	2.9	5x11	2.9	5x11	2.9	-	-	-	-
0.33		5x11	4.2	5x11	4.2	5x11	4.2	-	-	-	-
0.47		5x11	8	5x11	8	5x11	8	5x11	12	5x11	12
1		5x11	14	5x11	14	5x11	15	5x11	17	6.3x11	17
2.2		5x11	20	5x11	21	5x11	22	6.3x11	26	6.3x11	33
3.3		5x11	26	5x11	28	5x11	30	6.3x11	32	6.3x11	43
4.7		5x11	32	5x11	34	5x11	36	6.3x11 8x11	36 42	8x11	51
6.8		5x11	40	5x11	42	6.3x11	47	8x11	56	10x12	63
10		5x11	50	5x11	51	6.3x11	60	8x11 10x12	75 78	10x12 10x15	83 90
22		5x11	75	5x11 6.3x11	75 85	6.3x11 8x11	98 105	10x15	105	10x20	135
33		5x11 6.3x11	90 95	6.3x11 8x11	105 115	8x11 10x12	145 155	10x20	170	13x21	180
47		6.3x11	120	6.3x11 8x11	145 155	10x12 10x15	170 180	13x21	210	13x21 13x26	220 230
68		8x11	155	8x11	185	10x15	240	13x26	280	16x26	300
100		8x11	200	10x12	240	10x20	290	13x26 16x26	320 330	16x26	360
220		10x12 10x15	350 380	10x17 10x20	400 430	13x26 16x26	530 560	16x36	580	18x36	590
330		10x17 10x20	450 470	13x21	570	16x26	680	18x31	710	18x36	740
470		13x21	610	13x21 13x26 16x26	640 700 720	16x26 16x31	840 860	18x41	880	22x42	890
560		13x21	660	13x26	770	16x36	880	-	-	-	-
680		13x26	770	16x26	880	16x36	920	-	-	-	-
820		13x26	850	16x26	920	18x31	970	-	-	-	-
1000		13x26 16x26	900 1010	16x32 16x36	1190 1220	18x41	1250	-	-	-	-
1500		16x31	1300	18x31	1350	22x42	1500	-	-	-	-
2200		18x36	1550	18x36	1590	25x44	1880	-	-	-	-
2700		18x36	1610	22x42	1720	-	-	-	-	-	-
3300		18x36	1780	22x42	1900	-	-	-	-	-	-
4700		22x42	2050	25x44	2200	-	-	-	-	-	-
5600		25x42	2160	-	-	-	-	-	-	-	-
6800		25x44	2280	-	-	-	-	-	-	-	-

Ripple Current(mA,rms)at105□120Hz

Case Size WV {SV} uF	Ø D x L (mm)																	
	250		{300}		350		{400}		400		{450}		450		{500}			
	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple		
0.47	5x11	12	6.3x11	15	6.3x11	15	6.3x11	15	6.3x11	15	6.3x11	15	6.3x11	15	6.3x11	15		
1	6.3x11	17	6.3x11	20	8x11	22	8x11	22	8x11	22	8x11	22	8x11	22	8x11	22		
2.2	8x11	38	10x12	39	10x12	39	10x12	39	10x12	39	10x12	39	10x12	39	10x12	39		
3.3	8x11	43	10x12	53	10x12 10x15	53	53	55	10x15	53	55	10x15 10x20	53	55	10x15 10x20	53	55	
4.7	10x12	51	10x12 10x15	63	66	10x15	69	64	10x15	69	64	10x20	64	10x20	64	64		
6.8	10x12	70	10x15	79	10x15	85	10x15	85	10x15	85	10x20	75	10x20	75	10x20	75		
10	10x15	90	10x20	110	10x15 10x20 13x21	100 112 115	13x21 13x26	92	98	13x21 13x26	92	98	13x21 13x26	92	98	13x21 13x26	92	98
22	10x20	160	13x26	180	13x21 16x26	170 190	16x26	175	180	13x21 16x26	170 190	16x26 16x31	175 180	16x26 16x31	175 180	16x26 16x31	175 180	
33	13x21 13x26	175	180	16x26	190	16x26	220	16x26	210	16x26	220	16x36	210	16x26	210	16x36	210	
47	13x26	240	16x31	250	16x31	300	16x31	280	16x31	300	16x36	280	16x31	280	16x36	280		
68	16x26	320	16x31	330	16x36	355	16x36	330	16x36	355	18x36	330	16x36	330	18x36	330		
100	16x31	400	18x36	420	18x36	450	18x36	420	18x36	450	-	-	18x36	450	-	-		
120					18x31	440												

Ripple Current(mA,rms)at105□120Hz