

FEATURES

- WATERTIGHT
- INDESTRUCTIBLE
- FOR PROFESSIONAL USE
- PROTECTIVE
- MILITARY GRADE
- WITH PRE-CUBED FOAM
- STACKABLE

RS PRO Flight Cases & Equipment Cases

RS Stock No.: 2537423, 2537424, 2537426, 2537427, 2537428, 2537429, 2537430, 2537431, 2537432, 2537433, 2537434, 2537435, 2537436, 2537437, 2537438, 2537439



Airtight containers, resistant to chemicals, moisture and dust. Resistant to the most extreme temperatures (-33 ° C / + 90 ° C).

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

WATERPROOF CASE IN COPOLYMER POLYPROPYLENE

Indestructible cases recommended for professional use.

REMOVABLE LID WITH SAFETY LOCK

To remove the cover, simply tilt it at 70 ° after releasing the screws on the hinges rear

REINFORCED HINGES WITH ANTI CORROSION METAL PIN

STURDY CLOSURES

SEALING O-RING AND MANUAL PRESSURE RELEASE VALVE

ID REMOVABLE PLATE

ANTI TILT SUPPORTS (in some models)

WITH PRECUBED FOAM INSIDE


SELF OILING FREE RUNNING WHEELS

EASY TO OPEN RELEASE TELESCOPIC HANDLE

TWO MAN LIFT SIDE HANDLES

General Specifications

METRIC MM-KG-C°



INTERNAL DIMENSIONS

L LENGTH	580 mm
W WIDTH	440 mm
D DEPTH	330 mm
LID	60 mm
BASE	270 mm


EXTERNAL DIMENSIONS

L LENGTH	670 mm
W WIDTH	510 mm
D DEPTH	372 mm

OTHER DATA

WEIGHT EMPTY	10.54 Kg
WEIGHT WITH FOAM	12.65 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	84.20 lt
BUOYANCY	62 Kg/max
OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS

L LENGTH	22 13/16 in
W WIDTH	17 5/16 in
D DEPTH	13 in
LID	2 3/8 in
BASE	10 5/8 in

EXTERNAL DIMENSIONS

L LENGTH	26 3/8 in
W WIDTH	20 1/16 in
D DEPTH	14 5/8 in

OTHER DATA

WEIGHT EMPTY	23.23 lbs
WEIGHT WITH FOAM	27.88 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	22.19 gal
BUOYANCY	136.68 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max +194