



ENGLISH

Datasheet

RS Pro Incandescent V10994 Series Beacon, Flashing, Surface Mount, 12 V dc, 24 V dc

RS Stock No: **235-477**



Product Details

RS Pro flashing filament beacon provides great visibility through incandescent lighting for all applications. The beacon has 12/24 V dc voltage rating depending on bulb selected and produces 80 flash per minute. This beacon supports full internal suppression for maximum interference reduction and offers high quality solutions for industrial environments and process applications. It measures 207 x 166 mm. Beacon has a strong housing construction with IP56 degree of protection. It features surge protection for safety against peak voltage. The beacon has an optional cage guard that is suitable for three-point mounting version.

Features and Benefits

- Approximately 80 flash per minute
- 60 W light output where bulb is supplied
- IP56 rated
- Optional cage guard for three-point mounting versions
- Surge protection for safety against peak voltage
- Full internal suppression for maximum interference reduction
- Diameter of 166 mm



ENGLISH

Specifications:

Bulb Type	Incandescent
Current Type	DC
Housing Colour	Black
Lamp Included	No
Lens Colour	Lens Not Included
Light Effect	Flashing
Standards Met	RoHS Compliant
Base Diameter	153 mm
Height	190 mm
Maximum Temperature	+50°C
Minimum Temperature	-30°C
IP Rating	IP56
Mounting Style	3 Point
Supply Voltage	12/24 V dc
Flash Rate	75 fp/min