## Product data sheet Characteristics

# E8431\_1\_WE\_G2 16AX/20A 1Gang 1way full-flat switch with Onindicator White





Main	
Range	ZENcelo
Product or component type	Switch
Switch function	1-way
Device application	Control
Number of gangs	1 gang

#### Complementary

Device mounting	Flush	
	Surface	
Type of packing	Blister	
Clamping connection capacity	3 x 2.5 mm² for solid cable(s)	
	3 x 2.5 mm <sup>2</sup> for stranded cable(s)	
	4 x 1.5 mm <sup>2</sup> for solid cable(s)	
	4 x 1.5 mm <sup>2</sup> for stranded cable(s)	
Rated current	20 A/16 AX at 250 V AC 50/60 Hz	
Local signalling	Mechanical indicator (amber)	
Material	Grid plate: polycarbonate + GF 20 %	
	Base: polycarbonate	
	Cover: polycarbonate	
	Surround: polycarbonate	
Load type	Resistive	
	Incandescent lamp	
	Fluorescent lamp	
	Inductive	
Colour tint	White (RAL 9003)	
Connections - terminals	Brass rod terminals	
Width	87 mm	
Height	87 mm	
Depth	31 mm	

#### Environment

Ambient air temperature for operation	-535 °C
Relative humidity	095 %
Environmental characteristic	Dust resistant
Operating altitude	2000 m
Standards	IEC 60669-1 GB 16915.1 SS 227-1 EN 60669-1 MS IEC 60669-1

## Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	97.625 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	15 cm
Package 2 Width	19 cm
Package 2 Length	8 cm
Package 2 Weight	781 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	7810 g

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	