

ENGLISH

Datasheet

RS Pro 9 Way Right Angle Through Hole Mount PCB Dsub Connector Socket RS Stock No: 437-5522



Product Details

RS Pro D-sub connector socket has 90° mounting zinc passivated types with plastic feet for additional support. This right angle socket with 9 contacts has polyester housing. The through hole PCB mount socket has 5 A current rating and 750 V ac/dc voltage rating.

Features and Benefits

- Machined contacts
- 90° mounting zinc passivated types with plastic feet for additional support
- Female connector



ENGLISH

Specifications:

| Body Orientation | Right Angle |
|--|--|
| Contact Material | Copper Alloy |
| Contact Plating | Gold |
| Current Rating | 5 A |
| Gender | Female |
| Housing Material | PET |
| Maximum Operating Temperature | +125°C |
| Minimum Operating Temperature | -55°C |
| Manuatian Tura | T I I I I I |
| Mounting Type | Through Hole |
| Number of Contacts | 9 |
| | • |
| Number of Contacts | 9 |
| Number of Contacts Voltage Rating | 9 750 V ac/dc |
| Number of Contacts Voltage Rating Contact Resistance | 9 750 V ac/dc 5 mΩ |
| Number of Contacts Voltage Rating Contact Resistance Insulation Material | 9 750 V ac/dc 5 mΩ Glass Filled PET |
| Number of Contacts Voltage Rating Contact Resistance Insulation Material Insulation Resistance | 9 750 V ac/dc 5 m Ω Glass Filled PET 5 x 10 ⁹ Ω |