



## Main

Range	Pieno
Product or component type	Switch
Device application	Control
Switch application	Switch
Load type	Resistive Fluorescent
Cover frame colour tint	White

## Complementary

Device mounting	Surface Flush
Switch function	2-way
Number of rocker	4
Rated current	10 AX at 250 V AC 50 Hz
Local signalling	Fluorescent
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm <sup>2</sup> for stranded cable(s) 2 x 2.5 mm <sup>2</sup> for solid cable(s)
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

## Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	MS IEC 60669-1 BS EN 60669-1 GB 16915.1 SS 227-1 IEC 60669-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.6 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	124 g
Unit Type of Package 2	CAR
Number of Units in Package 2	60
Package 2 Height	21 cm

Package 2 Width	32.5 cm
Package 2 Length	50 cm
Package 2 Weight	7418.4 g
Unit Type of Package 3	PAL
Number of Units in Package 3	1200
Package 3 Height	86 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	153420 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>